H361

Safety switch, heavy duty, fusible, 30A, 3 poles, 20 hp, 20 hp, 600 VAC/DC, NEMA 1





Main

Product	Single Throw Safety Switch
Current Rating	30 A
Number of Poles	3
Voltage Rating	600 V AC/DC
Wire Size	AWG 12AWG 6 aluminium AWG 14AWG 6 copper
Disconnect Type	Fusible disconnect
Short Circuit Current Rating	10 KA H or K 200 kA R, J or L
Mounting Type	Surface
Factory Installed Neutral	None
Electrical Connection	Lugs
Duty Rating	Heavy duty
Certifications	UL listed file E2875
Enclosure Rating	NEMA 1 steel

Complementary

Maximum Horse Power Rating	5 Hp 480 V AC 5060 Hz 3 phase NEC 240.6	
	15 Hp 480 V AC 5060 Hz 3 phase NEC 430.52	
	7.5 Hp 600 V AC 5060 Hz 3 phase NEC 240.6	
	20 Hp 600 V AC 5060 Hz 3 phase NEC 430.52	
	5 Hp 250 V DC	
	15 hp 600 V DC	
Maximum Width	7.55 in (191.77 mm)	
Height	14.6 in (370.84 mm)	
Depth	4.87 in (123.70 mm)	
Tightening torque	45 Lbf.ln (5.08 N.m) 0.02 in ² (13.3 mm ²) AWG 6)	
	4.52 N.M for 8.367 mm ² (AWG 8)	
	3.95 N.m for 2.065.261 mm² (AWG 14AWG 10)	

Ordering and shipping details

and an analysis and an analysi		
Category	00008 - H&HU SW,2&3P,N1,30-200A	
Discount Schedule	DE1	
GTIN	00785901481843	
Nbr. of units in pkg.	1	
Package weight(Lbs)	8.04 lb(US) (3.65 kg)	
Returnability	Yes	
Country of origin	US	

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	5.20 in (13.208 cm)	
Package 1 width	7.70 in (19.558 cm)	
Package 1 Length	16.20 in (41.148 cm)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	120	
Package 2 Weight	990.00 lb(US) (449.056 kg)	
Package 2 Height	45.00 in (114.3 cm)	

Package 2 width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	☐ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes

Contractual warranty

Contraction Warranty	
Warranty	18 months

Approximate Dimensions

