

HBL2420SW -- Twist-Lock Watertight Safety-Shroud Receptacle



3P4W, 20A 3PH 250V, L15-20R, Watertight Housing & Flange

Product Specifications

Product Type



Product Item	Single Receptacle
Wiring Scheme	3-Pole, 4-Wire Grounding
Amperage	20A
Voltage	3 Phase 250V AC
NEMA Configuration	L15-20R
Item Style	Shrouded Watertight
Device Color	Gray
Horsepower	3
Terminal Retainer Material	Clear polycarbonate
Housing Material	Impact modified PBT

Terminal Clamp Material	Steel, nickel plated .080" Curved, scalloped
Terminal Screw Material	#10-32 Brass (white finish on neutral screw when used) Multi-drive
Ground Screw Material	#10-32 Brass (Green)
Body Contact Carrier Material	Natural White Nylon
Contact Spring Material	.031" Brass
Spring Binding Plate Material	.031" Brass
Mounting Screw Material	Stainless Steel 302/304 Multi-drive
Ground Contact Material	.031" Brass
Rivet Material	Steel
Ratings	Molded In or Stamped On
Catalog No	Permanently ink marked on product
Dielectric Voltage Withstand	2,000V minimum
Current Interrupting	Certified for current interrupting at full rated current
Temperature Rise	Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
Terminal Accommodation	20A #12AWG
Terminal Identification	Terminals identified in accordance with UL 498 (X, Y, Z, White, Green)
Flammability	VO per UL94 or CSA 22.2 No. 0.6
Operating Temperatures	Maximum Continuous 75 C Minimum -40 C (w/o impact)
Moisture Resistance	Type 4, 4X, 12, IP66 suitability
Flange Gasket Material	Closed-cell Neoprene foam
Lid Gasket Material	Closed-cell Neoprene foam
Cover Hinge Pin Material	Stainless Steel 302/304
Housing and Flange Material	Gray Valox
Cover Spring Material	Stainless Steel 302/304
Listings	FED SPEC UL/CSA
Catalog Page	Click here for catalog page B21
Brochures	Click here for product brochure
Catalog Section	Click here for Section-B
UPC Number	783585231341

Weight in LBs

0.6



NEMA L15-20R
20A 3Ø 250V AC
UL/CSA
3 HP

NEMA
Configuration

