


HBL2510 -- Twist-Lock Receptacle



4P5W, 20A 3PH 120/208V AC, L21-20R, Black Nylon Face

HBL2510

Product Specifications

Product Type



Twist-Lock Devices

| | |
|----------------------------------|---|
| Product Item | Single Receptacle |
| Wiring Scheme | 4-Pole, 5-Wire Grounding |
| Amperage | 20A |
| Voltage | 3 Phase Y 120/208V AC |
| NEMA Configuration | L21-20R |
| Item Style | Standard |
| Device Color | Black |
| Horsepower | 2 |
| Terminal Clamp Material | .040" (1.0) Brass |
| Terminal Screw Material | #10-32 Bronze (White finish on neutral screw when used) |
| Ground Screw Material | #10-32 Bronze (Green) |
| Contact Spring Material | .040" Brass |
| Mounting Screw Material | Steel-zinc-plated |
| Cover (Top) Material | Black Nylon |
| Base Material | Nylon Polyester |
| Ground Contact Material | .040" Brass |
| Bridge (Mounting Strap) Material | .050" Brass |
| Back Plate Material | .040" Brass |
| Rivet Material | Brass |
| Auto Ground Clip Material | Stainless Steel |
| Ratings | Molded In or Stamped On |
| Catalog No | Permanently ink marked on product |
| Dielectric Voltage Withstand | 2,000V minimum |
| Current Interrupting | Certified for current interrupting at full rated current |
| Temperature Rise | Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75. |
| Terminal Accommodation | #14 to #8 AWG Copper Only |
| Terminal Identification | Terminals identified in accordance with UL 498 (X, Y, Z, White, Green) |
| Flammability | UL 94 VO for Receptacles and Inlets. HB or better for Plugs and Connectors. |
| Operating Temperatures | Maximum Continuous 75 C Minimum -40 C (w/o impact) |
| Listings | FED SPEC UL/CSA |
| UPC Number | 783585235851 |
| Weight in LBs | 0.3 |
| Link to Drawing Library | Click here for Library |
| Link to PDF Catalog | Click here for Catalog |



NEMA Configuration

