



# HBL2810 -- Twist-Lock Receptacle



4P5W, 30A 3PH 120/208V AC, L21-30R, Black Nylon Face

## Product Specifications

<p><b>Product Type</b></p>	
<p><b>Product Item</b></p>	<p>Single Receptacle</p>
<p><b>Wiring Scheme</b></p>	<p>4-Pole, 5-Wire Grounding</p>
<p><b>Amperage</b></p>	<p>30A</p>
<p><b>Voltage</b></p>	<p>3 Phase Y 120/208V AC</p>
<p><b>NEMA Configuration</b></p>	<p>L21-30R</p>
<p><b>Item Style</b></p>	<p>Standard</p>
<p><b>Device Color</b></p>	<p>Black</p>
<p><b>Horsepower</b></p>	<p>3</p>
<p><b>Terminal Clamp Material</b></p>	<p>.040" (1.0 )Brass</p>
<p><b>Terminal Screw Material</b></p>	<p>#10-32 Bronze (White finish on neutral screw when used)</p>
<p><b>Ground Screw Material</b></p>	<p>#10-32 Bronze (Green)</p>
<p><b>Contact Spring Material</b></p>	<p>.040" Brass</p>
<p><b>Mounting Screw Material</b></p>	<p>Steel-zinc-plated</p>
<p><b>Cover (Top) Material</b></p>	<p>Black Nylon</p>
<p><b>Base Material</b></p>	<p>Nylon Polyester</p>
<p><b>Ground Contact Material</b></p>	<p>.040" Brass</p>
<p><b>Bridge (Mounting Strap) Material</b></p>	<p>.050" Brass</p>
<p><b>Back Plate Material</b></p>	<p>.040" Brass</p>
<p><b>Rivet Material</b></p>	<p>Brass</p>
<p><b>Auto Ground Clip Material</b></p>	<p>Stainless Steel</p>
<p><b>Ratings</b></p>	<p>Molded In or Stamped On</p>
<p><b>Catalog No</b></p>	<p>Permanently ink marked on product</p>
<p><b>Dielectric Voltage Withstand</b></p>	<p>2,000V minimum</p>
<p><b>Current Interrupting</b></p>	<p>Certified for current interrupting at full rated current</p>
<p><b>Temperature Rise</b></p>	<p>Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.</p>
<p><b>Terminal Accommodation</b></p>	<p>30A #10 AWG</p>
<p><b>Terminal Identification</b></p>	<p>Terminals identified in accordance with UL 498 (X, Y, Z, White, Green)</p>
<p><b>Flammability</b></p>	<p>HB or better per UL 94 or CSA 22.2 No. 0.6</p>
<p><b>Operating Temperatures</b></p>	<p>Maximum Continuous 75 C Minimum -40 C (w/o impact)</p>
<p><b>Listings</b></p>	<p>FED SPEC UL/CSA</p>
<p><b>UPC Number</b></p>	<p>783585236230</p>
<p><b>Weight in LBs</b></p>	<p>0.3</p>
<p><b>Link to Drawing Library</b></p>	<p><a href="#">Click here for Library</a></p>
<p><b>Link to PDF Catalog</b></p>	<p><a href="#">Click here for Catalog</a></p>

