



## Non-NEMA Twist-Lock® Devices 30 Ampere, 250, 125/250 Volts and 3Ø Y 120/208 Volts AC Insulgrip® Plugs, Flanged Inlets, Connector Bodies and Receptacles



**HBL3331GC**




**HBL3334C**



**HBL3431C**

For Replacement Use Only

**IP20**  
SUITABILITY



**30A 250V**  
Non-NEMA  
Not UL listed



**30A 125/250V**  
Non-NEMA  
Not UL Listed

### Insulgrip Plugs

Description	Cord Dia.	Catalog Numbers
Black and white nylon.	.360"-.930" (9-24)	<b>HBL3331GC</b> <b>HBL3331C</b>

Accessories on page B-51.


### Insulgrip Flanged Inlets

Description	Catalog Numbers
Nylon casing, back wired.	- <b>HBL3334C</b>

Accessories on page B-50.

For Replacement Use Only

**IP20**  
SUITABILITY



**30A 3Ø 250V AC**  
Non-NEMA  
Not UL Listed



Non-NEMA  
**30A 3Ø Y**  
**120/208V AC**  
Not UL Listed

### Insulgrip Plugs

Description	Cord Dia.	Catalog Numbers
Black and white nylon.	.35"-1.15" (9-29)	<b>HBL3431GCB</b> <b>HBL3431C</b>

Accessories on page B-53.

Notes: For technical information see page B-69.

The devices shown on this page are not listed by Underwriters Laboratories Inc. and are for replacement use only in existing installations.

**CAUTION:** To avoid electrical shock, review premises carefully and do not use if slot or blade configuration (design) is already in a circuit having a rating differing from the rating of this device.