



WIRING DEVICE-KELLEMS

(/wiringdevice-kellems/en/myList)

(/wiringdevice-kellems/en/)

- Home (/Wiringdevice-Kellems/En/) / Products (/Wiringdevice-Kellems/En/Products/CI/DataHub_WebRoot_WDK)
- / Electrical & Electronic (/Wiringdevice-Kellems/En/Products/Electrical-Electronic/CI/535411_WDK)
- / Wiring Devices (/Wiringdevice-Kellems/En/Products/Electrical-Electronic/Wiring-Devices/CI/559793_WDK)
- / Pin & Sleeve (/Wiringdevice-Kellems/En/Products/Electrical-Electronic/Wiring-Devices/Pin-Sleeve/CI/2027807_WDK)
- / IEC Mechanical Interlocks (/Wiringdevice-Kellems/En/Products/Electrical-Electronic/Wiring-Devices/Pin-Sleeve/IEC-Mechanical-Interlocks/C/2027812_WDK) / HBL460MI5W

HBL460MI5W

by Hubbell Wiring Device-Kellems
Catalog ID: HBL460MI5W



SHARE

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Female, Mechanically Interlocked Receptacle, 60A 3-Phase Delta 600V AC, 3-Pole 4-Wire Grounding, Terminal Screws

More Information

Where to Buy

Search Location

WHERE TO BUY

[Contact Us \(/contactUs\)](#)

Overview ()



Product Details ()



General

Application	High Ampacity Watertight Connections
Color	Black
Environmental Conditions	Watertight
Item Type	Mechanically Interlocked Single
Material	Thermoplastic/Composite
Material - Mounting Hardware	Screw Mount
Number Of Poles	3-Pole
OEM Brand Name	Hubbell Wiring Device-Kellems
Performance	<ul style="list-style-type: none"> Electrical - Current Interrupting - Certified for current interrupting at full rated current and voltage Electrical - Dielectric Voltage - Withstands 3,000V AC Min Electrical - Max. Working Voltage - 600V AC RMS Environmental - Flammability - UL94-5VA and V-0 Classification Environmental - Ingress Protection - IP67 Suitability Environmental - Moisture Resistance - Outdoor - 4X (Watertight, Washdown) Indoor - 12 (Dust-tight, Falling Dirt and Noncorrosive Liquids). Environmental - Operating Temperature - Max. Continuous +75°C Min. Continuous -40°C Mechanical - Impact Resistance - In accordance with UL 746C Mechanical - Mounting - External adjustable feet Mechanical - Product Identification - Identification and ratings are part of the external label and molded into the receptacle mount Mechanical - Terminal Identification - In accordance with UL, CSA and international conventions
Series	Unfused Circuit-Lock
Style	Standard Service
Type	Mechanical Interlock
UPC	783585406046
Voltage Rating Description	3 Phase 600V AC

Dimensions

Display Size	Standard Sized Product
--------------	------------------------

Current Related

Amperage Rating	60 A
Connectivity	Pressure Screw Terminals
Current / Amperage Rating	60 A
Current Rating	60
Phase	Three Phase
Voltage Rating	3 Phase 600 VAC

Wattage	36000
---------	-------

Conductor Related

Number Of Wires	4-Wire
Wire Size	#8 AWG to #2 AWG

Certifications and Compliance

Industry Standard(s)	<ul style="list-style-type: none"> • CSA Certified • UL Listed
Nema Rating	Non-NEMA

Resources / Downloads ()



WHERE TO BUY



SUPPORT



OUR COMPANY



SALES CORNER



(/wiringdevice-kellems/en/)

Wiring Device - Kellems is a proud member of the Hubbell family.

Click to learn more.

© 2017 Hubbell. All Rights Reserved

Privacy Policy (/hubbell/en/terms-of-use#99)

Terms of Use (/hubbell/en/terms-of-use)



(https://twitter.com/HUBBELLELECSYS) (https://www.youtube.com/user/HubbellElectricalSys)