



IP20
SUITABILITY




Connector Bodies

Description	Cord Dia.	Catalog Number			
Insulgrip connector body, black and white nylon. Multiple drive screws.	.230"-.720" (5.8-18.3)	HBL4729C	HBL4579C	HBL4779C	
All black nylon.	.230"-.720" (5.8-18.3)	HBL4729CBK	-	-	
Insulgrip connector body, 8 position angle, black and white nylon. Multiple drive screws.	.325"-.655" (8.3-16.6)	HBL4729CA	-	-	
Insulgrip connector body, corrosion resistant, yellow and white nylon. Multiple drive screws.	.230"-.720" (5.8-18.3)	HBL47CM29C	HBL45CM79C	HBL47CM79C	
Elastogrip connector body, yellow elastomer, dust tight.	.300"-.655" (7.6-16.6)	HBL2547	-	-	
Elastogrip® connector body, yellow elastomer, water/dust tight.	.300"-.655" (7.6-16.6)	HBL25W47**	-	-	
Valise® connector body, yellow nylon.	.220"-.660" (5.6-16.8)	HBL4729VY	HBL4579VY	HBL4779VY	
Valise® connector body, black nylon.	.220"-.660" (5.6-16.8)	HBL4729VBK	HBL4579VBK	HBL4779VBK	


Note: See page B-49 for accessories.



HBL4729C



HBL25W47




HBL4729VY


Receptacles

Description	Catalog Number			
Duplex, flush, brown RTP face, back and side wired.	HBL4700*	HBL4550*	HBL4750*	
Duplex, flush, ivory RTP face, back and side wired.	HBL4700I*	-	-	
Duplex, ring terminal connection.	HBL4700RT*	HBL4550RT*	-	
Duplex, isolated ground, flush, orange RTP face, back and side wired.	IG4700A*	IG4550A*	-	
Duplex, corrosion resistant, yellow RTP face, back and side wired.	HBL47CM00*	-	-	
Single, flush, black nylon face, back and side wired.	HBL4710	HBL4560	HBL4760	
Same as HBL4760 without mounting screws, ears. Terminal screws backed out, back and side wired.	-	-	HBL4760C	
Single, ring terminal connection.	HBL4710RT	HBL4560RT	-	
Single, isolated ground, flush, orange nylon face, back and side wired.	IG4710	IG4560	-	
Single, black nylon face mounted on a 4" (101.6) round box cover, back and side wired.	HBL4711	-	HBL4761	
Single, panel mount, black nylon face, side wired only, 1.75" or 1.937" (44.5 or 49.2) mounting centers.	HBL4713	HBL4563	HBL4763	

Note: See pages B-48 and B-49 for accessories.



HBL4700



HBL4710

Flanged Receptacles

Description	Catalog Number			
Insulgrip flanged receptacle, nylon casing, back wired.	HBL4715C	HBL4585C	HBL4785C	
Stainless steel casing, brown phenolic.	HBL4715	HBL4585	HBL4785	
Corrosion resistant, stainless steel casing, yellow melamine.	HBL47CM15	-	-	

Note: See pages B-48 and B-49 for accessories.


HP ratings are AC only.

RTP is an abbreviation for reinforced thermoplastic polyester.


See section M for additional information on isolated ground devices.

*Supplied with break-off tabs for split circuit wiring.

**Watertight connector body IP55 suitability when closure plug is inserted or when installed and used properly with watertight plug.



HBL4715



HBL4715C

Dimensions in Inches (mm)