

HBL5242 -- Straight Blade Products, Heavy Duty Intermediate Grade Duplex Receptacle



2-Pole 3-Wire Grounding, 15A 125V, 5-15R, Flush Nylon Face, Side Wired Only, Brown

Product Specifications

Product Type	<p>Flush Receptacles</p>
Receptacle Style	Duplex
Face Shape	Traditional
Standard	NEMA
Amperage	15A
Voltage	125V
Poles and Wires	2 Pole, 3-Wire Grounding
Wiring Method	Side Wire Only
Hospital Grade ?	No
Receptacle Grade	Heavy Duty Spec Grade
Face Style	Finder Groove
Color	<p>Brown</p>
Other Available Colors	Brown, Gray, Ivory, White,
NEMA No.	5-15R
Horsepower	0.5
Type	2 Pole, 3 Wire, Grounding
Rating	15A, 125V
Certification	UL Listed, File E2186, Guide RTRT Fed Spec WC596G, Meets NEMA WD-6 requirements Listed to UL Standard 498, Certified to CSA, C22.2, No. 42 where applicable
Terminal Screw Material	#8-32 Brass /Ni plated for neutral
Ground Screw Material	#8-32 Brass, Multiple Drive (Green)
Top Material	Nylon
Base Material	Reinforced PET
Power Contacts Material	.037" (.9) Phosphor Bronze
Mounting Strap Material	.050" (1.3) Brass
Auto Ground Clip Material	Stainless Steel
Mounting Screw Material	Steel-Zinc Plated
Dielectric Voltage	Withstands 2,000V minimum.
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%..
Terminal Identification	Terminals identified in accordance with UL498 (Brass, White, Green).
Terminal Accommodation	#14-#10 AWG copper stranded or solid conductor only.
Product Identification	Ratings are a permanent part of the device.
Flammability	Top: UL 94 V2. Base: UL 94 V0 and UL 94-5 VA.
Operating Temperatures	Maximum continuous 75°C, minimum -40°C (w/o impact).
UPC Number	783585434667
Weight in LBs	0.200
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

