



HBL5364VY -- Straight Blade Products, Valise Plug



2-Pole 3-Wire Grounding, 20A 125V, 5-20P, Yellow Nylon.

Product Specifications

Product Type	 <p>Plugs</p>
Body Style	Straight
Standard	NEMA
Amperage	20A
Voltage	125V
Poles and Wires	2 Pole, 3-Wire Grounding
Hospital Grade ?	No
Plug/Connector Grade	Valise
Color	 <p>Yellow</p>
NEMA No.	5-20P
Horsepower	1
Cord Dia.	.220"-.660" (5.6-16.8)
Type	2 Pole, 3 Wire, Grounding
Rating	20A,125V
Certification	UL Listed to UL498 File E1706, CSA Certified to C22.2 No. 42 File 280
IP Suitability	IP20
Housing Material	Nylon - Yellow
Cord Clamp Material	Noryl (Polyphenylene Oxide)
Contact Blades Material	.060" (1.5) Brass
Ground Contact Blade Material	.040" (1.0) Copper Alloy
Terminal Screw Material	Steel (copper or nickel finish)
Ground Screw Material	Steel (green finish)
Dielectric Voltage	Withstands 2,000V minimum.
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%..
Terminal Identification	Terminals identified in accordance with UL498 (Brass, White, Green).
Terminal Accommodation	#18-#10 AWG copper stranded conductor
Product Identification	Permanent part of device
Flammability	UL 94 V2
Operating Temperatures	Maximum continuous 75°C, minimum -40°C (w/o impact).
UPC Number	783585013169
Weight in LBs	0.100
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

