

# Straight Blade Devices


## 15 and 20 Ampere, 125 Volts

2 Pole, 3 Wire Grounding

### Insulgrip®, Elastogrip® and Valise® Plugs




HBL5266C




HBL5266CA




HBL1447



HBL14W47



HBL5965VY



HBL5966VBLK

**IP20**  
SUITABILITY



15A 125V  
NEMA 5-15P  
UL CSA



20A 125V  
NEMA 5-20P  
UL CSA

## Plugs

### Insulgrip

Description	Cord Diameter	Catalog Numbers	
Black and white nylon.	.230"-.720" (5.8-18.3)	HBL5266C	HBL5366C
Blue and white nylon.	.230"-.720" (5.8-18.3)	HBL5266CBL	-
Black nylon extra large cord clamp.	.360"-.720" (9.1-18.3)	HBL5266EBK	HBL5366EBK
Corrosion resistant yellow nylon.	.230"-.720" (5.8-18.3)	HBL52CM66C	HBL53CM66C
8-position angle plug, black and white nylon.	.325"-.655" (8.3-16.6)	HBL5266CA	HBL5366CA
8-position angle plug, transparent enclosure.	.325"-.655" (8.3-16.6)	HBL5266CAT	-
Anchor lock, black & white nylon. <sup>(1)</sup>	.230"-.720" (5.8-18.3)	HBL5280C	-
Anchor lock, corrosion resistant yellow nylon. <sup>(1)</sup>	.230"-.720" (5.8-18.3)	HBL52CM80C	-
Finger grip, black neoprene, combination screws. CSA only.	.312"-.468" (7.9-11.9)	HBL5921	-
Fusible, black vinyl housing, slotted screws. CSA only.	.296"-.625" (7.5-15.9)	HBL5299	-

## IP20 and IP55

SUITABILITY

### Elastogrip®

Description	Cord Diameter	Catalog Numbers	
Yellow elastomer, dust tight.	.300"-.655" (7.6-16.6)	HBL1447	HBL1433
Yellow elastomer, watertight.	.300"-.655" (7.6-16.6)	HBL14W47*	HBL14W33*

**IP20**  
SUITABILITY

### Valise®

Description	Cord Diameter	Catalog Numbers	
Yellow nylon.	.220"-.660" (5.6-16.8)	HBL5965VY	HBL5364VY
Black nylon.	.220"-.660" (5.6-16.8)	HBL5965VBLK	HBL5364VBK
Gray nylon.	.220"-.660" (5.6-16.8)	HBL5965VGY	-
Orange nylon, sold in bulk pack of 50.	.220"-.660" (5.6-16.8)	HBL515PVO	-
Insulation displacement terminals, black nylon.	.230"-.360" (5.8-9.1)	HBL5966VBLK	-
Insulation displacement terminals, yellow nylon.	.230"-.360" (5.8-9.1)	HBL5966VY	-

Notes: Horsepower ratings listed are AC only.

\*Watertight plugs IP55 suitability when installed and used properly with mating Elastogrip watertight connector bodies.

See page A-45 for accessories.

<sup>(1)</sup> UL Component Listed only. Not for general use applications.