

# HBL5666VY -- Straight Blade Products, Valise Plug



2-Pole 3-Wire Grounding, 15A 250V, 6-15P, Yellow  
Nylon

HBL5666VY

## Product Specifications

### Product Type



Plugs

### Body Style

Straight

### Standard

NEMA

### Amperage

15A

### Voltage

250V

### Poles and Wires

2 Pole, 3-Wire Grounding

### Hospital Grade ?

No

### Plug/Connector Grade

Valise

### Color



Yellow

### NEMA No.

6-15P

### Horsepower

1.5

### Cord Dia.

.220"-.660" (5.6-16.8)

### Type

2 Pole, 3 Wire, Grounding

### Rating

15A, 250V

### Certification

UL Listed to UL498 File E1706, CSA Certified to C22.2 No. 42 File 280

### IP Suitability

IP20

### Housing Material

Nylon - Yellow

### Cord Clamp Material

Noryl (Polyphenylene Oxide)

### Contact Blades Material

.060" (1.5) Brass

### Ground Contact Blade Material

.040" (1.0) Brass

### Terminal Screw Material

Steel (copper or nickel finish)

### Ground Screw Material

Steel (green finish)

### Dielectric Voltage

Withstands 2,000V minimum.

### Current Interrupting

Certified for current interrupting at full rated current.

### Temperature Rise

Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%..

### Terminal Identification

Terminals identified in accordance with UL498 (Brass, White, Green).

### Terminal Accommodation

#18-#10 AWG copper stranded or solid conductor only.

### Product Identification

Ratings are a permanent part of the device.

### Flammability

UL 94 HB or better.

### Operating Temperatures

Maximum continuous 75°C, minimum -40°C (w/o impact).

### Certified

UL2305 OEM and replacement use on convention center flat cable cord sets.

### UPC Number

783585013053

### Weight in LBs


0.150

### Link to Drawing Library

[Click here for Library](#)

### Link to PDF Catalog

[Click here for Catalog](#)



NEMA Configuration

