


HBL7571 -- Twist-Lock Connector Body



2P3W, 15A 125V, ML-2R, Angled Body, Nylon Cover, Phenolic Body, Black

Product Specifications

Product Type	<p>Twist-Lock Devices</p>
Product Item	Connector Body
Wiring Scheme	2-Pole, 3-Wire Grounding
Amperage	15A
Voltage	125V AC
NEMA Configuration	ML-2R
Item Style	Standard
Device Color	Black
Cord Dia.	.335"-.421" (8.5-10.7)
Housing Material	Black nylon
Cord Clamp Material	Black Nylon
Terminal Screw Material	#8-32 Brass
Ground Screw Material	#8-32 Brass (green finish)
Cord Clamp Screw Material	Steel - black oxide
Body Holding Screw Material	Steel, zinc plated
Body Contact Carrier Material	Black Thermoset
Contact Spring Material	.032" (.8) Bronze
Ground Contact Material	.032" Bronze
Ratings	Molded In or Stamped On
Catalog No	Permanently ink marked on product
Dielectric Voltage Withstand	2,000V minimum
Current Interrupting	Certified for current interrupting at full rated current
Temperature Rise	Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
Cord Accommodation	Round portable service cords of diameters commensurate with the device rating as defined in UL Standard 62, CSA C22.2 No. 49.
Terminal Accommodation	15A #14 AWG
Terminal Identification	Terminals identified in accordance with UL 498 (X, Y, Z, White, Green)
Flammability	UL 94 VO for Receptacles and Inlets. HB or better for Plugs and Connectors.
Operating Temperatures	Maximum Continuous 75 C Minimum -40 C (w/o impact)
Moisture Resistance	IP20
Listings	UL/CSA
UPC Number	783585237695
Weight in LBS	0.1
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog



NEMA Configuration

