


Twist-Lock® Devices
15 Ampere, 125, 125/250 Volts
Midget Twist-Lock Connector Bodies
and Flanged Receptacles



IP20
SUITABILITY



Connector Bodies

Description	Cord Dia.	Catalog Numbers
Valise® connector body, black nylon, polarized.	.220"-.385" (5.6-9.8)	HBL7464V - -
Valise® connector body, black nylon, insulation displacement terminals.	.300"-.430" (7.6-10.9)	- HBL7593V -
Black nylon cover, phenolic body, screw terminals.	.281"-.421" (7.1-10.7)	- HBL7593 -
Angle connector body, black nylon cover, phenolic body, screw terminals.	.335"-.421" (8.5-10.7)	- HBL7571 -
Valise® type, black nylon, with insulation displacement terminals, multiple drive screws.	.300"-.430" (7.6-10.9)	- - HBL7484V
Black nylon body, phenolic base, multiple drive screws, cord grip.	.281"-.421" (7.1-10.7)	- - HBL7484
Same as above, except for angle cord grip.	.335"-.421" (8.5-10.7)	- - HBL7433

Accessories on page B-6.

Flanged Receptacles


Description	Catalog Numbers
Stainless steel flange, exposed terminals.	HBL7468 - -
Exposed terminals, black nylon flange.	- HBL7596N -
Exposed terminals, stainless steel flange.	- HBL7596 -
Covered terminals, stainless steel flange, accepts cord .500" (12.7) in dia.	- HBL7598 -
Exposed terminals, black nylon flange.	- - HBL7487N
Exposed terminals, stainless steel flange.	- - HBL7487
Covered terminals, stainless steel flange, accepts cord .500" (12.7) in diameter.	- - HBL7489

Accessories on page B-6.

Notes: Male ML-2R devices have solid center ground pins.
 Male ML-3R devices have hollow center neutral sleeves.



HBL7464V



HBL7593V



HBL7593




HBL7571



HBL7484V




HBL7484




HBL7596



HBL7598



HBL7596N



HBL7468

