



HBL9758VY -- Straight Blade Products, Valise Plug



2-Pole 2-Wire Non-Grounding, 20A 250V, 2-20P, Yellow Nylon

Product Specifications

Product Type	 Plugs
Body Style	Straight
Standard	NEMA
Amperage	20A
Voltage	250V
Poles and Wires	2 Pole, 2 Wire Non-Grounding
Hospital Grade ?	No
Plug/Connector Grade	Valise
Color	 Yellow
NEMA No.	2-20P
Horsepower	2
Cord Dia.	.220"-.660" (5.6-16.8)
Type	2 Pole, 3 Wire, Grounding
Rating	15A,125V
Certification	UL Listed to UL498 File E1706, CSA Certified to C22.2 No. 42 File 280
IP Suitability	IP20
Housing Material	Nylon
Cord Clamp Material	Noryl (Polyphenylene Oxide)
Contact Blades Material	Brass
Terminal Screw Material	Steel (copper or nickel finish)
Dielectric Voltage	Withstands 2,000V minimum.
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%..
Terminal Identification	Terminals identified in accordance with UL498 (Brass, White, Green).
Terminal Accommodation	#18-#14 AWG copper stranded or solid conductor only.
Product Identification	Ratings are a permanent part of the device.
Flammability	UL 94 V2.
Operating Temperatures	Maximum continuous 75°C, minimum -40°C (w/o impact).
UPC Number	783585013312
Weight in LBs	0.150
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

