

Cross reference

RoHS/LF P/N Search

Industry Standards

Alphabetical List

Documentation

3D model search

Customer drawing search

Multi Selection Search

Search by category

HM2P67PDE125N9

HM2P67PDE125N9


HM2P67PDE125N9 - CompactPCI®, Millipacs® : 2 mm Hard Metric Series 5 Row vertical Press-Fit Header, Type AB 19 with 95 Signal Pins

Distributor Stock

Print Datasheet

FCI Brings You More

Contact our sales/technical support  
Sample request



Customer drawing

Product Environmental Compliance Report

Specifications

Download document

Alternate Products

## General Dimensional Electrical Mechanical Physical Approvals / Certifications Mounting Other Features

## General

Gender	Header
Number of contacts	89
Number of rows	5
Orientation	Vertical
Product Type	Header
Series	Module Type AB (15.4 mm) 19 Pos
Shielded	Yes
Number of levels (Contact)	Refer to Customer Drawing

## Dimensional

Length (Tail)	Rear Mating Tail Level 1 (13 mm)
---------------	----------------------------------

## Electrical

Current rating	1.5A at 20°C, 1A at 70°C
Resistance (Contact)	20 milli ohms max.
Resistance (Insulation)	10,000 M-ohms min.
Voltage rating	750V rms

## Mechanical

Withdrawal Force	0.15N min. per Contact Pair
Hertz stress	200 Kpsi min.
Mating force (Signal)	0.75N max. per Contact Pair

## Physical

Finish (Contact)	Level 2
Material (Contact)	Copper alloy
Material (Housing)	Thermoplastic (UL94 V-0)
Temperature (Operating - range)	-55°C to +125°C

## Approvals / Certifications

Approvals / Certifications	UL Approved
UL File Number	E66906

## Mounting

Mounting style (Board)	Press-Fit
------------------------	-----------

## Other Features

Packaging (Type)	Tray
------------------	------

Disclaimer : The information above is for reference only. For more technical details, refer to product specification and application specification.