

Cross reference

RoHS/LF P/N Search

Industry Standards

Alphabetical List

Documentation

3D model search

Customer drawing search

Multi Selection Search

Search by category


HM2R71PA510FN9

HM2R71PA510FN9

HM2R71PA510FN9 - Millipacs® : 2 mm Hard Metric Millipacs series-5-row Receptacle Module Type B (19 Pos)

Distributor Stock

Print Datasheet



Customer drawing

Product Environmental Compliance Report

Specifications

Download document

Alternate Products

FCI Brings You More

[Contact our sales/technical support](#)  
[Sample request](#)
**Dimensional General Electrical Mechanical Physical Mounting Other Features**
**Dimensional**
**Length (Tail)** Press-Fit Tail (2.8 mm)

**General**
**Gender** Receptacle

**Number of contacts** 95

**Number of rows** 5

**Orientation** Right Angle

**Product Type** Receptacle

**Series** Module Type B (19 Pos)

**Shielded** Yes

**Number of levels (Contact)** Refer to Customer Drawing

**Electrical**
**Current rating** 1.5A at 20°C, 1A at 70°C

**Resistance (Contact)** 20 milli ohms max.

**Resistance (Insulation)** 10,000 M-ohms min.

**Voltage rating** 750V rms

**Mechanical**
**Withdrawal Force** 0.15N min. per Contact Pair

**Hertz stress** 200 Kpsi min.

**Mating force (Signal)** 0.75N max. per Contact Pair

**Physical**
**Finish (Contact)** Level 2

**Material (Contact)** Copper alloy

**Material (Housing)** High Temperature Thermoplastic (UL94 V-0)

**Temperature (Operating - range)** -55°C to +125°C

**Mounting**
**Mounting style (Board)** Press-Fit

**Other Features**
**Packaging (Type)** Tray

Disclaimer : The information above is for reference only. For more technical details, refer to product specification and application specification.