

Representative

 Catalog Number:
 HS500-1000-4

 Product ID:
 7TAA017090R0009

 UPC Number:
 78621087207

 EAN Number:
 05414363152934

Status: Active

Heavy-Wall Heat-Shrinkable Tubing for Cable Range 250 - 500 kcmil, Expanded Diameter 2 Inch, Length 48 Inch, 600 Volt, 90 Degrees Continuous Use, Cross-Linked Polyolefin with Thermoplastic Adhesive Liner, Black

- Made of thermally stabilized cross-linked polyolefin, enabling a recovered wall thickenss greater than that of the cable jacket replaced.
- Withstands severe mechancial requirements of U.R.D., submersible, and direct burial installations.
- Tubing, featuring an internally applied sealant, offers protection against moisture, and may be used over lead, steel, aluminum, copper, standard plastic and elastomeric insulating materials.

North American Specifications (UNSPSC)		
UNSPSC	39121723 Heat shrinkable tube	
IGCC	5073 Heat shrinkable tube	
Brand Name	Shrink-Kon	
Туре	Heavy-Wall Heat-Shrinkable Tubing	
Special Features	Made of thermally stabilized cross-linked polyolefin,	
	enabling a recovered wall thickenss greater than	
	that of the cable jacket replaced.	
Voltage Rating	600V	
Length	48 in	
Color	Black	

European Specifications (ETIM)		
ETIM	EC000217 Shrink tubing	
Туре	Heat-shrink	
Model	Thick-walled	
Shrink rate	3:1	
Inner diameter before heat-shrink	50.8mm	
Inner diameter after heat-shrink	16.002mm	
Nominal diameter inch	2 inch	
Wall thickness after shrinking	3.556mm	
Length	1.2192m	
Operation temperature	-55-+110°C	
Colour	Black	
Material	Polyolefin (PO-X)	
Halogen free	N	
With inner glue	N	
Printable	N	
UL approval	Υ	

Packaging	
Outer Quantity	2
Outer Dimensions (inches)	4x49x4
Weight Uom	125 lbs. per 100

Documents / Support Tools	
Technical Drawing / Data Sheet	WSD-000473
Technical Drawing / Data Sheet Canada	Available on Website
Safety Data Sheet (SDS) Global	SDS-00046-TB2



For further technical assistance, please contact us...

ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com ABB Installation Products Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com