

Heat Shrink Tubing

Flexible Halogen-Free Polyolefin

pro-POWER

RoHS
Compliant



Characteristics:

- Halogen-Free
- Operating temperature -55°C to +125°C
- Minimum shrink temperature : +70°C
- Full recovery temperature : +120°C
- Shrink Ratio 3:1
- Meets Sony-SS-00259
- Colour : Black

Applications:

This heat shrink tubing is manufactured with modified radiation cross-linked polyolefin. The specially designed halogen-free formulation makes the tubing very flexible and shrinks at lower temperatures. Suitable for applications where temperature sensitive components protection, e.g. PVC jacketed wire and cable, and quick shrinkage is required. Offers good mechanical and electrical performances.

Technical Data:

Property	Test Method	Typical Data
Tensile Strength	ASTM D 2671	≥10.4 MPa
Ultimate Elongation	ASTM D 2671	≥200%
Longitudinal Shrinkage	UL 224	±5%
Heat Aging Tensile Strength Ultimate Elongation	158°C, 168 hrs	≥7.3 MPa ≥100%
Heat Shock	250°C, 4 hrs	No cracking, No dripping
Flammability	FMVSS302	Pass
Dielectric Strength	ASTM D150	≥15kV/mm
Volume Resistivity	ASTM D2671	≥1 × 10 ¹⁴ Ωcm
Copper Stability	UL224	Pass
Copper Corrosion	UL224	No corrosion

Part Number Table

Description	Size		As Supplied	After Recovery		Part Number	
	Inch	mm	Internal Diameter Min(mm)	Internal Diameter(mm)	Wall Thickness(mm)	(1.22 m Length)	(5 m Length)
Heat Shrink Tubing Flexible Halogen-Free Polyolefin	1/16	1.5	1.5	0.5	0.45	HS510-1.22M	HS510-5M
	1/8	3	3	1	0.55	HS511-1.22M	HS511-5M
	3/16	4.5	4.5	1.5	0.6	HS512-1.22M	HS512-5M
	1/4	6	6	2	0.65	HS513-1.22M	HS513-5M

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER

Heat Shrink Tubing

Flexible Halogen-Free Polyolefin



Description	Size		As Supplied	After Recovery		Part Number	
	Inch	mm	Internal Diameter Min(mm)	Internal Diameter(mm)	Wall Thickness(mm)	(1.22 m Length)	(5 m Length)
Heat Shrink Tubing Flexible Halogen-Free Polyolefin	3/8	9	9	3	0.75	HS514-1.22M	HS514-5M
	1/2	12	12	4	0.75	HS515-1.22M	HS515-5M
	3/4	18	18	6	0.85	HS516-1.22M	HS516-5M
	1	24	24	8	1	HS517-1.22M	HS517-5M
	1-1/2	39	39	13	1.5	HS518-1.22M	HS518-5M

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.