Search Results Page 1 of 2



Network and Electrical Solutions

UNIFIED PHYSICAL INFRASTRUCTURESM



Home Industries **Solutions**

Products Partners Support

About Us

Careers

-Search-

Entire Site

Search Results

Evaluate

- FAQ's

How to Buy

- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Within Results

▼ Text Search: 'HSTT09-CC'

Your search criteria matched only one product, shown below

HSTT09-CC



Flexible Ployolefin DRY-SHRINK™Heat Shrink Tubing

- General Purpose heat shrink tubing for dry locations
- Applications include insulating, protecting, harnessing and identifying wires.
- Material Type: Crosslinked Polyolefin
- Shrink Ratio: 2:1
- Temperature Range: -67°F to 275°F (-55°C to 135°C)
- Flammability Rating: Flame retardant EXCEPT clear
- Voltage: 600 V
- UL Recognized, CSA Certified
- Mil Spec: AMS-DTL-23053/5 Class 1 (Colors) Class 2 (Clear)

- Part Number
- RoHS Compliancy Status
- Part Description
- Material
- Color
- Military Specification
- Length Per Reel (ft.)

HSTT09-CC

Compliant

Thin Wall Polyolefin Heat Shrink

Polyolefin cross-linked

Clear

AMS-DTL-23053/5 Class 2

100

Search Results Page 2 of 2

Length Per Reel (m)	30.5
Max. Recovered I.D. (In.)	.046
Max. Recovered I.D. (mm)	1.2
Min. Expanded I.D. (In.)	.093
Min. Expanded I.D. (mm)	2.4
 Nominal Diameter / Size 	.093
 Nominal Recovered Wall Thickness (In.) 	.020
 Nominal Recovered Wall Thickness (mm) 	.5
 Pricing Description 	Heat Shrink Thin, .09"(2.4mm) Dia, Clear
■ Shrink Ratio	2:1
■ Temperature Range	-67°F to 275°F (-55°C to 135°C)
Min. Order UOM	RL
Min. Order Qty.	1
■ BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Home | Industries | Solutions | Products | Partners | Support | Contact Us | Site Map | Careers Copyright © 1995-2008, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy