

Products

- Products Overview
- Product Search**
- Evaluate
 - FAQ's
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Product Search >

Current refinements (click  to remove) Search Tips

Part Number > HSTT100-48-5-10

Your search criteria matched only one product, shown below

HSTT100-48-5-10



- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
 - Cross-linked, UV resistant material improves flame retardancy, chemical, and temperature resistance
- For clear, add "C" to end of part number package suffix (Example HSTT05-48-QC). Contact customer service for additional color information.

Meets Mil Spec AMS-DTL-23053/5 Class 1(Colors), Class 2 (Clear)

Part Number	HSTT10048-5-10
RoHS ComplianceStatus	Compliant
Part Description	Thin Wall Polyolefin HeatShrink
Material	Flame retardantpolyolefin cross-linked except clear
Color	White
CSA Certified	Yes
Military Specification	AMS-DTL-23053/5 Class 1
UL Recognized	E122770
Length (ft.)	4
Length (m)	1.2
CE Compliant	No
CE Marking	No
FlammabilityRating	Flame Retardant
Max. Recovered I.D. (In.)	.500
Max. Recovered I.D. (mm)	12.7
Min. Expanded I.D(In.)	1.00
Min. Expanded I.D(mm)	25.4
Nominal Diameter Size	1.00
Nominal RecoveredWall Thickness (In.)	.035
Nominal RecoveredWall Thickness (mm)	.9
Pricing Description	Heat Shrink Thin,1"(25.4mm) Dia, White
Shrink Ratio	2:1
Temperature Range	-67°F to 275°F (-55°C to 135°C)
Min. OrderUOM	PC
Min. OrderQty.	5
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	<input type="button" value="e"/>

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.