



enabling technologies

[10 Gig Ethernet](#)
[Data Centers](#)
[Fiber System Deployment](#)
[Grounding System for Data Centers](#)
[Industrial Ethernet](#)
[Managing the Physical Layer](#)
[Network Security](#)
[Power Over Ethernet](#)

product information

[Products](#)
[Bill of Material](#)
[My Catalog](#)
[Part Search](#)
[Cross Reference](#)
[FAQ's](#)
[Download / Request Literature](#)
[Downloads](#)

resources to help you

[Evaluate Technologies](#)
[Design a Solution](#)
[How to Buy](#)
[Evaluate, Design & Install Products](#)
[Download Panduit Logo](#)
[White Papers](#)
[RoHS Compliance](#)

value added services

[Strategic Alliance Program](#)
[Consultants](#)
[Distributors](#)
[Installers](#)
[System Integrators](#)
[Warranties](#)

Product Information: Products

[USA](#) | [Heat Shrink & Abrasion Protection](#) | [Heat Shrink](#) | [General Purpose, Flexible Polyolefin for Dry Locations](#) |
HSTT Heat Shrink 4 ft (1.2M) Pieces



evaluate

[FAQs](#)

design a solution

install & maintain

- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
- Cross-linked, UV resistant material improves flame retardancy, chemical, and temperature resistance

For clear, add "C" to end of part number package suffix (Example HSTT05-48-QC). Contact customer service for additional color information.

^ Meets Mil Spec AMS-DTL-23053/5 Class 1.

| | |
|--|---|
| Part Number | HSTT12-48-Q |
| Product Family | HSTT Heat Shrink 4 ft (1.2M) Pieces |
| RoHS Compliant | Compliant |
| Part Description | Thin Wall Polyolefin Heat Shrink |
| Material | Flame retardant polyolefin cross-linked except clear [^] |
| Color | Black [‡] |
| CSA Certified | Yes |
| Military Specification | AMS-DTL-23053/5 Class 1 |
| UL Recognized | E122770 |
| Length (Ft.) | 4 |
| Flammability Rating | Flame Retardant |
| Max. Recovered I.D. (In.) | .062 |
| Max. Recovered I.D. (mm) | 1.6 |
| Min. Expanded I.D. (In.) | .125 |
| Min. Expanded I.D. (mm) | 3.2 |
| Nominal Diameter / Size | 1/8 |
| Nominal Recovered Wall Thickness (In.) | .020 |
| Nominal Recovered Wall Thickness (mm) | .5 |
| Shrink Ratio | 2:1 |
| Std. Pkg. UOM | PK |
| Temperature Range | -67°F to 275°F (-55°C to 135°C) |
| UOM | PC |

| | |
|-----------------------|----|
| Std. Pkg. Qty. | 25 |
| Min. Order Qty | 25 |
| BOM Qty. (# of Pkgs.) | |

Add to My Catalog

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.

[legal information](#) | [privacy policy](#) | [site map](#)

Copyright © 1995-2005, PANDUIT CORP. All rights reserved.