



[support](#) | [locate distributor](#) | [about panduit](#) | [careers](#) | [worldwide](#)

World Leader in Network and Electrical Solutions

Printer Friendly

[HOME](#) | [SOLUTIONS](#) | [RESOURCES](#) | [PRODUCTS](#) | [SERVICES](#) | [LEARNING](#)

SEARCH



[Search Tips](#)

Current refinements (click to remove)

[Region](#) ▶ [USA](#) [Product Family](#) ▶ [HSTT Heat Shrink 4 ft. Pieces](#) [Text Search: 'HSTT38-48-QC'](#)

Your search criteria matched only one product, shown below.



- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
- Cross-linked, UV resistant material improves flame retardancy, chemical, and temperature resistance

For clear, add "C" to end of part number package suffix (Example HSTT05-48-QC). Contact customer service for additional color information.

* Meets Mil Spec AMS-DTL-23053/5 Class 1 (Colors), Class 2 (Clear)

Part Number:	HSTT38-48-QC
RoHS Compliancy Status:	Compliant
Part Description:	Thin Wall Polyolefin Heat Shrink
Material:	Flame retardant polyolefin cross-linked except clear*
Color:	Clear
Military Specification:	AMS-DTL-23053/5 Class 2
Length (ft.):	4
Length (m):	1.2
Max. Recovered I.D. (In.):	.187
Max. Recovered I.D. (mm):	4.8
Min. Expanded I.D. (In.):	.375
Min. Expanded I.D. (mm):	9.5
Nominal Diameter / Size:	3/8
Nominal Recovered Wall Thickness (In.):	.025
Nominal Recovered Wall Thickness (mm):	.6
Shrink Ratio:	2:1
Temperature Range:	-67°F to 275°F (-55°C to 135°C)
Min. Order UOM:	PC
Min. Order Qty.:	25
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to My Catalog	<input type="checkbox"/>

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.

[View Content Details](#)

Evaluate

Design a Solution

Install & Maintain

Installation Instructions:

[Pan-Shrink Heat Shrink - In001 pdf](#)

[legal information](#) | [privacy policy](#) | [site map](#)

Copyright © 1995-2007, PANDUIT CORP. All rights reserved.