

## Accessories - IC-DFR 12 - 1852121

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Accessories, Number of positions: 12, Pitch: 5.08 mm, Color: green, This assembly frame can only be used in combination with IC 2,5/...-STGF-5,08

### Product Features

- Feed-through assembly frame for inverted COMBICON plug IC 2,5-STGF-5,08
- Vibration-resistant screw connection for both plugs provided by screw flanges
- Fitting the MSTB 2,5/...-STF-5,08 plug from outside
- Frame in plate cutout can be used and screwed on.
- Snap-locking of the IC plug into the frame
- Up to a panel thickness of 1.5 mm, the frame can be screwed before the IC plug is mounted



### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
GTIN	 4 017918 109004
Weight per Piece (excluding packing)	3.168 g
Custom tariff number	39269097
Country of origin	Poland

### Technical data

#### Dimensions

Pitch	5.08 mm
Dimension a	55.88 mm

#### General

Range of articles	IC-DFR
Insulating material group	I

## Accessories - IC-DFR 12 - 1852121

### Technical data

#### General

Nominal cross section	2.5 mm <sup>2</sup>
Insulating material	PA
Flammability rating according to UL 94	V0
Number of positions	12

#### Standards and Regulations

Flammability rating according to UL 94	V0
----------------------------------------	----

### Classifications

#### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402

#### ETIM

ETIM 3.0	EC000879
ETIM 4.0	EC000879
ETIM 5.0	EC002310


#### UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409


### Drawings

## Accessories - IC-DFR 12 - 1852121

Drilling diagram



Dimensional drawing



Dimension b: 10.84 mm + (no. of pos. x 5.08 mm)

Dimension c: Dim. b + 5.83 mm