
Thomas@Betts





J973

UPC Number: 78621081567

Status: Active

Description:

Non-Insulated Tubular Ring Terminal, Length 1.99 Inches, Width .84 Inches, Bolt Hole 3/8 Inch, Wire Range 1/0AN-2/0, Copper, Tin Plated, 50 Pack




US Cutsheet PDF Catalog Link http://www-public.tnb.com/contractor/docs/

stakon.pdf



General



These non-insulated ring terminals are made of electrolytic copper for high conductivity. They can be installed with crimping tools having a single indentor or double indentor (recommended for solid

wire).

General	
Insulation Type	Non-Insulated - Tubular
Terminal Series	J
Material	Copper
Finish	Electro -Tin Plated
Color	Metallic
Wire Range	1/0AN-2/0
Stud Size	3/8
Dimension Information	
Ote als Thisters are	00
Stock Thickness	.06
A (inches)	1.99
B (inches)	.84
C (inches)	.53
M (inches)	1.58
Specifications	
Temperature Rating	150°C
Voltage Rating	600V
Flammability Rating	UL 94 V-0
MIL Specification	MS-20659-118
Tooling	
Tool Charts	Available on Website
Application Tools	TBM6, TBM6S, WT3185
Recommended Tool	TBM6S
Packaging	
T&B Order Multiple	50
T&B Inner Pack	50
Package in Units	500
Package Type	Standard
T&B Sold in UOM	Each
T&B Weight Per UOM	6.5 lbs. per 100
Application Support	
T&B Sales Drawings	wsd-000219



Overview Available on Website
Wire Guide Tables Available on Website

Notes

Not available on Mylar Tape.

Certifications

RoHS Compliance Yes

Certifications





File Nbr: E9809

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com