

Detailed information for: KC6-22Z-04

This page contains technical data sheet, documents library and links to offering related to this product. If you require any other information, please contact us using form located at the bottom of the page.

[Print...](#)

[Print to Pdf...](#)

Data Sheet

Documentation

KC6-22Z-04

General Information

Extended Product Type: KC6-22Z-04

Product ID: GJH1213001R0224

EAN: 4013614049675

Catalog Description: KC6-22Z-04 Mini Contactor Relay 110-125VDC

Long Description: The KC6-22Z mini contactor relay is a compact 4 pole contactor relay with screw terminals. They are ideally suited for applications where reliability is a must and space is at a premium. Mini contactors relays are used in residential buildings, commercial buildings and industrial applications for switching of control signals up to 3 A / 400 V (AC-15). Further features are the noiseless and hum-free coil and a switch position indication.

Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Mini Contactors



Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Popular Downloads

Data Sheet, Technical Information:	1SBC100173C0201
Dimension Diagram:	GJL1200436F0001

Dimensions

Product Net Width:	52.5 mm
Product Net Height:	57.5 mm

Product Net Depth:	46.5 mm
Product Net Weight:	0.175 kg
Technical	
Number of Poles:	4
Mini Contactor Type:	Mini Contactor Relay
Rated Operational Voltage:	Auxiliary Circuit 12 ... 240 V DC Auxiliary Circuit 12 ... 500 V AC/DC Auxiliary Circuit 690 V
Rated Frequency (f):	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC Control Circuit DC Main Circuit 60 Hz Main Circuit 50 Hz Main Circuit DC
Rated Impulse Withstand Voltage (U _{imp}):	Auxiliary Circuit 6 kV
Rated Insulation Voltage (U _i):	690 V acc. to UL/CSA 600 V
Number of Main Contacts NC:	0
Number of Main Contacts NO:	0
Number of Auxiliary Contacts NC:	2
Number of Auxiliary Contacts NO:	2
Rated Operational Current AC-15 (I _e):	(120 V) 4 A (220 / 240 V) 4 A (240 V) 4 A (24 V) 4 A (380 / 400 V) 3 A (500 V) 2 A
Rated Operational Current DC-13 (I _e):	(110 V) 0.7 A (220 / 240 V) 0.4 A (24 V) 2.5 A
Conventional Free-air Thermal Current (I _{th}):	Auxiliary Circuit 6 A
Rated Control Circuit Voltage (U _c):	110 ... 125 V DC
Coil Operating Limits:	(acc. to IEC 60947-5-1) for DC supply 0.85 ... 1.1 x U _c (at θ ≤ 55 °C)
Degree of Protection:	Auxiliary Circuit Terminals IP20 Control Circuit Terminals IP20
Mechanical Durability:	10000000 cycle
Minimum Switching Capacity:	17 V 5 mA
Maximum Electrical Switching Frequency:	AC-15 600 cycles per hour DC-13 600 cycles per hour
Connecting Capacity Auxiliary Circuit:	Flexible with Ferrule 1/2x 1 ... 2.5 mm ² Flexible with Insulated Ferrule 1/2x 1 ... 2.5 mm ² Flexible 1/2x 1 ... 2.5 mm ² Rigid 1/2x 1 ... 4 mm ²
Connecting Capacity Control Circuit:	Flexible with Ferrule 1/2x 1 ... 2.5 mm ² Flexible with Insulated Ferrule 1/2x 1 ... 2.5 mm ² Flexible 1/2x 1 ... 2.5 mm ² Rigid 1/2x 1 ... 4 mm ²
Wire Stripping Length:	Auxiliary Circuit 9 mm
Tightening Torque:	Auxiliary Circuit 0.8 ... 1.1 N·m

Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
------------------------------	--

Power Loss:	at Rated Operating Conditions per Pole 2 W
--------------------	--

Standards:	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1
-------------------	--

Environmental

Ambient Air Temperature:	Operation -25 ... +55 °C Storage -40 ... +80 °C
---------------------------------	--

Maximum Operating Altitude Permissible:	2000 m
--	--------

Resistance to Shock acc. to IEC 60068-2-27:	11 ms Pulse 15g
--	-----------------

Resistance to Vibrations acc. to IEC 60068-2-6:	3g / 3 ... 150 Hz
--	-------------------

RoHS Status:	Following EU Directive 2011/65/EC
---------------------	-----------------------------------

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Auxiliary Circuit 600 V AC/DC
--	-------------------------------

General Use Rating UL/CSA:	(600 V AC) 5 A
-----------------------------------	----------------

Contact Rating UL/CSA:	A600
-------------------------------	------

Connecting Capacity Auxiliary Circuit UL/CSA:	Stranded 1/2x 22-10 AWG
--	-------------------------

Tightening Torque UL/CSA:	Auxiliary Circuit 7 in·lb Control Circuit 7 in·lb
----------------------------------	--

Certificates and Declarations (Document Number)

CB Certificate:	1SAA938001-2001
------------------------	-----------------

CCC Certificate:	1SAA938000-3804
-------------------------	-----------------

cUL Certificate:	1SAA938002-1701
-------------------------	-----------------

Declaration of Conformity - CE:	1SAD938512-0001
--	-----------------

EAC Certificate:	1SAA938001-2701
-------------------------	-----------------

Instructions and Manuals:	2CDC102047M6801
----------------------------------	-----------------

RMRS Certificate:	1SAA938001-0704
--------------------------	-----------------

RoHS Information:	1SAD938512-0001
--------------------------	-----------------

UL Certificate:	1SAA938002-1601
------------------------	-----------------

Container Information

Package Level 1 Units:	10 piece
-------------------------------	----------

Package Level 1 Width:	115 mm
-------------------------------	--------

Package Level 1 Height:	54 mm
--------------------------------	-------

Package Level 1 Length:	280 mm
--------------------------------	--------

Package Level 1 Gross Weight:	1.82 kg
--------------------------------------	---------

Package Level 1 EAN:	4013614410888
-----------------------------	---------------

Classifications

Object Classification Code:	K
ETIM 4:	EC000196 - Contactor relay
ETIM 5:	EC000196 - Contactor relay
ETIM 6:	EC000196 - Contactor relay
eClass:	7.0 27371001
UNSPSC:	39121500

Contact information

What would you like to do?

I need more information

ABB Sales ▲

Submit your inquiry

Country

United States of America ▼

Name

Company

E-Mail

Phone

Zip code

Your message

→ [Privacy policy](#)

Cancel

Send message

Your local ABB Sales Team

Name

Customer Support

▲ Close