

**Models L101, L102 & L111**

**One channel loggers with the ability to perform a variety of recording tasks**

**► FEATURES**

- Compatible standard current probes with voltage output and BNC connection (Models L101 & L102) see chart on pages 56 and 57 for compatible current probes
- Fused input (Model L111)
- Compatible with standard AC current probes with current output and banana plug connection (Model L111)
- 2 inputs (Model L102)
- 64 samples per cycle
- Programmable storage rates from 8 every second to 1 every day
- 4 user selectable storage modes
- Stores up to 240,000 measurements in non-volatile memory
- Powered by standard Alkaline batteries
- Lightweight, compact, fits anywhere
- 5 LED indicators quickly and clearly display logger status
- Includes FREE DataView® software for data storage, real-time display, analysis and report generation
- Isolated USB 2.0 communication cable included
- EN 61010-1; 50V CAT III

**► APPLICATIONS ( MODELS L101 & L111 )**

- Load profiling
- Fault current detection
- Intermittent problem detection
- Demand recording
- Neutral current monitoring
- Harmonic current recording using DataView® software
- Metering CT resizing
- Start-Stop time stamping

**► APPLICATIONS ( MODEL L102 )**

- Split phase load monitoring
- Neutral & ground current monitoring
- Intermittent problem detection
- Harmonic current monitoring using DataView® software
- Machine load monitoring
- Start-Stop time stamping



**► SPECIFICATIONS**

MODELS	L101	L102	L111
<b>ELECTRICAL</b>			
Channels	One	Two	One
Input Connection	BNC	One BNC connector per channel	Two recessed banana jacks
Measurement Range	0 to 1V <sub>AC</sub> (probe dependent)		0 to 1A <sub>AC</sub> (probe dependent)
Resolution	0.1mV		0.1mA
Accuracy (50/60Hz)	0 to 10mV: unspecified 10 to 50mV: ±(0.5% of Reading + 1mV) 50 to 1000mV: ±(0.5% of Reading + 0.5mV)		0 to 10mA: unspecified 10 to 50mA: ±(0.5% of Reading + 1mA) 50 to 1000mA: ±(0.5% of Reading + 0.5mA)
Input Impedance	800kΩ		1Ω
Sample Rate	64 samples/cycle		
Storage Rate	Programmable from 8 every second to 1 every day		
Storage Modes	Start/Stop, FIFO, Extended Recording Mode (XRM™)* and Alarm		
Recording Length	15 minutes to 8 weeks, programmable using DataView®		
Memory	240,000 measurements (512KB) The recorded data is stored in non-volatile memory and will be retained even if the battery is low or removed.		
Communication	USB 2.0 optically isolated		
Power Source	2 x 1.5V AA-cell Alkaline batteries (included)		
Battery Life	100 hours to >45 days (dependent on sample rate and recording length)		
<b>MECHANICAL</b>			
Dimensions	5.38 x 2.75 x 1.28" (136 x 70 x 32mm)	5.18 x 2.75 x 1.28" (132 x 70 x 32mm)	
Max Conductor Size	Current probe dependent		
Weight (with battery)	6.4 oz (181g)	6.64 oz (188g)	
Case	UL94-V0		
Vibration	IEC 68-2-6 (1.5mm, 10 to 55Hz)		
Shock	IEC 68-2-27 (30G)		
Drop	IEC 68-2-32 (1m)		

See pages 56 & 57 for current probe selection

CATALOG NO.	DESCRIPTION
2126.02	Simple Logger® II Model L101 (1-Channel, TRMS, 0 to 1V <sub>AC</sub> , DataView® software)
2126.03	Simple Logger® II Model L102 (2-Channel, TRMS, 0 to 1V <sub>AC</sub> , DataView® software)
2126.04	Simple Logger® II Model L111 (1-Channel, TRMS, 0 to 1A <sub>AC</sub> , DataView® software)

