



Actual

**Catalog Number:** L-5-30MH-9-M  
**Product ID:** 7TAG054680R0016  
**UPC Number:** 72849491530  
**EAN Number:** 05414363154075  
**Status:** A

Intermediate, Integrated Mounting Hole Cable Tie, Natural Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21 Rated for AH-2 Plenum, Length of 150.36mm (5.92 Inches), Width of 3.63mm (0.143 Inches), Thickness of 1.21mm (0.048 Inches), Tensile Strength Rating of 133 Newtons (30 Pounds), #8 Screw for Mounting

- Application Tools: ERG50, ERG120, QC-100, L-200, L-400-C

### North American Specifications (UNSPSC)

UNSPSC	39121703 Cable ties
IGCC	5034 Cable ties
Type	Intergrated Mounting Hole
Standard	UL E49405
Width	0.14 in ; 3.6 mm
Length	5.85 in ; 148.59 mm
Bundle Diameter	1.25 in ; 31.75 mm
Material	Nylon/Polyamide 6.6
Color	Natural
Lock Mechanism	Plastic Pawl
Tensile Strength	30 pounds ; 133 newtons

### European Specifications (ETIM)

ETIM	EC000046 Cable tie
Band width	3.63mm
Length belt/tape/tie	150.36mm
Tie thickness	1.21mm
Min. holding force	133N
Model	Internal toothing
Band closure	Plastic lip/-cam
Material	Plastic
Material quality	Polyamide PA
Surface protection	Untreated
Halogen free	Y
Colour	Natural colour
Transparent	N
Reflective (fluorescent)	N
Text strip	None
Solvable fastener	N
Type of fastening	Screw hole
MIL approval	N

### Packaging

Inner Quantity	1000
Inner Dimensions (inches)	13x11x3
Outer Quantity	10000
Outer Dimensions (inches)	17.2x13.2x10.75
Weight Uom	1.91 lbs. per 1000

### Documents / Support Tools

Technical Drawing / Data Sheet	TDS000443
--------------------------------	-----------

**For further technical assistance, please contact us...**

ABB Installation Products - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

ABB Installation Products Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)