

Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - PDFAL Mechanical ..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips

 Text Search: 'LAM3SB600-38-1Y'


Your search criteria matched only one product, shown below

LAM3SB60038-1Y



For Use with Stranded Aluminum or Copper Code Conductors

- Triple barrel provides termination of three conductors
- Vertical configuration saves space
- Made from high strength, extruded aluminum alloy to provide premium electrical and mechanical performance
- Tin-plated to inhibit corrosion
- Wide wire range -taking capability minimizes inventory requirements
- Inspection window to visually assure full conductor insertion
- Plated steel or aluminum set screw provides high strength, durable electrical contact between conductor and connector
- UL Listed and CSA Certified for use up to 600 V and UL temperature rated 90°C

Part Number	LAM3SB600-38-1Y
RoHS Compliancy Status	Compliant
Note	LAM3SB600-38-1Y replaces LAM3SB600-38-1
Part Description	Aluminum vertical configuration, three barrel, two-hole tongue connector, type LAM3SB.
Product Type	Mechanical Connectors- Lugs
Material	Tin-Plated Aluminum
Height (In.)	3.00
Height (mm)	76
Length (In.)	4.91
Length (mm)	124.7
Stud Hole Size (In.)	3/8
Stud Hole Spacing (In.)	1.38
Tongue Width (In.)	2.47
Aluminum or Copper Conductor Size Range	#2 AWG – 600 kcmil
CE Compliant	No
Hex Key Size (In.)	1/2
Pricing Description	Aluminum Mechanical Lug, 2 Hole, 3 Barrel, #2 AWG 600 kcmil, 3/8 (9.5mm) Stud
Tightening Torque (InLbs)	500
Tongue Length	2.34
Tongue Length (mm)	59.4
Tongue Thickness	0.75
Tongue Width (mm)	62.7
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.