


KEMET Part Number: LDEMG3220KA5N00
(DEMG3220KA5N00)



LDE, Film, Metallized PEN Stacked, Automotive Grade, 0.22 uF, 10%, 160 VAC, 400 VDC, 125°C, 5040, 3.8mm



General Information	
Series:	LDE
Dielectric:	Metallized PEN Stacked
Style:	SMD Chip
Features:	Automotive Grade
RoHS:	Yes
Qualifications:	AEC-Q200
AEC-Q200:	Yes
Component Weight:	1.2 g
Shelf Life:	104 Weeks
MSL:	2a

Dimensions	
Chip Size	5040
L	13mm +/-0.4mm
W	10.4mm +/-0.5mm
T	3.8mm MAX
B	0.4mm +0.5/-0.3mm

Packaging Specifications	
Packaging:	T&R
Packaging Quantity:	1250

Specifications	
Capacitance:	0.22 uF
Capacitance Tolerance:	10%
Voltage AC:	160 VAC
Voltage DC:	400 VDC
Temperature Range:	-55/+125°C
Rated Temperature:	125°C
Dissipation Factor:	0.8% 1kHz
Insulation Resistance:	1 GOhms
Max dV/dt:	100 V/us

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

