
(DEQG2470KA5N00)



LDE, Film, Metallized PEN Stacked, Automotive Grade, 0.047 uF, 10%, 250 VAC, 1000 VDC, 125°C, 5040, 4.1mm



Dimensions		
Chip Size	5040	
L	13mm +/-0.4mm	
W	10.4mm +/-0.5mm	
Т	4.1mm MAX	
В	0.4mm +0.5/-0.3mm	

Packaging Specifications		
Packaging:	T&R	
Packaging Quantity:	1250	

General Information		
Series:	LDE	
Dielectric:	Metallized PEN Stacked	
Style:	SMD Chip	
Features:	Automotive Grade	
RoHS:	Yes	
Qualifications:	AEC-Q200	
AEC-Q200:	Yes	
Component Weight:	1.2 g	
Shelf Life:	104 Weeks	
MSL:	2a	

Specifications		
Capacitance:	0.047 uF	
Capacitance Tolerance:	10%	
Voltage AC:	250 VAC	
Voltage DC:	1000 VDC	
Temperature Range:	-55/+125°C	
Rated Temperature:	125°C	
Dissipation Factor:	0.8% 1kHz	
Insulation Resistance:	1 GOhms	
Max dV/dt:	300 V/us	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

