

Multilayer Chip Inductors for High Frequency Applications (HK series)

HK1608R22J-T



■ Features

- Item Summary
0.22uH±5%, 0.3A, 0603/1608 (EIA/JIS)
- Lifecycle Stage
Mass Production
- Standard packaging quantity (minimum)
Taping paper 4000pcs

■ Products characteristics table

| | |
|-------------------------------|---------------|
| Inductance | 0.22 uH ± 5 % |
| Case Size (EIA/JIS) | 0603/1608 |
| Rated Current (max) | 0.3 A |
| DC Resistance (typ) | 0.95 Ω |
| DC Resistance (max) | 1.5 Ω |
| Q (min) | 8 |
| Q (typ) | 12 |
| LQ Measuring Frequency | 50 MHz |
| Self Resonant Frequency (min) | 400 MHz |
| Self Resonant Frequency (typ) | 600 MHz |
| Operating Temp. Range | -40 to +85 °C |
| RoHS2 Compliance (10 subst.) | Yes |
| REACH Compliance (168 subst.) | Yes |
| Soldering | Reflow/Wave |

■ External Dimensions

| | |
|-------------|--------------|
| Dimension L | 1.6 ±0.15 mm |
| Dimension W | 0.8 ±0.15 mm |
| Dimension T | 0.8 ±0.15 mm |
| Dimension e | 0.3 ±0.2 mm |

2016.05.13

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
 Before making final selection, please check product specification.