



- Product Line**
- ZConnect
 - Ceres Connectors
 - X-Lok Connectors
 - M Series Sensor Connectors**
 - > MPronto-12
 - > M8
 - > M10.5
 - > M12
 - > M20
 - > M23
 - > Distribution Box
 - > Guided M8
 - FLOS & FLOS+ Connectors
 - Power Connectors
 - RBL Connectors
 - HS-Lok Connectors
 - NMEA 2000 Connectors
 - RJ Connectors
 - USB Connectors
 - D-SUB Connectors
 - SSL Solution Connectors
 - HDMI Connectors
 - DVI Connectors
 - Fiber Optic Connectors
 - Cable Joiner
 - FICX Connectors
 - Cable Gland - Anti-UV
 - Vent
 - LED Indicator
 - CNC Products
 - Product Applications**
 - Product Search**

Home > Product Line > M Series Sensor Connectors > M12



Part Number : M12A-03BFFA-SL8001

Share 0 Tweet

Pin : Copper Alloy,Gold Plated

Connector Body : Thermoplastic, UL Recognized.;Zn Alloy ,Nickel Plated

Temperature Range : -40°C~+105°C

Download:

- Sample 3D model(.stp)
- Sample 3D model(.igs)

Add to inquiry list Check inquiry list Submit inquiry

Description	Details
Connector	M12 A Code
Connector Gender	Female connector
Mating Style	Screw Thread
Current Rating	4A
No. of Contacts	3 pins
Contact Gender	Female pin
Field installable	Field Installable (Solder)
Connector body type	Without strain relief
Backshell	Straight
Waterproof Rating	IP68
Cable OD Φ	4.5~6.5
Voltage rating	250V AC/DC

* Design and specifications are subject to change without notice. update: 2021-03-02 00:00:00

