

“Stay Connected” with



Liquid Tight Cordgrips

a PennEngineering® Company

## Heyco® -Tite Liquid Tight Cordgrips

Multi-Hole with Integral Sealing Ring

Sequenced by Conductor Size

The Ultimate in Liquid Tight Strain Relief Protection

**NO O-RING  
REQUIRED!**



CONDUCTORS		NPT HUB*		PG HUB**		METRIC HUB**				
Hole Size mm.	No.	UL or cULus	Black Part No.	Desc.	Black Part No.	Desc.	Black Part No.	Desc.		
<b>Round, Open Holes – consult Heyco for Snap-in-2 Hub versions</b>										
4,2	2		M3231GAB	LTCG 1/2	M3216GAB	LTCG 13	M4340GAB	LTCG M20		
4,5	9	cULus	M8437GBF†	LTCG 1	M3225GBF	LTCG 29	M4348GBF	LTCG M32		
			M4524GBG†	LTCG 1-1/4	M3204GBG	LTCG 36	M4352GBG	LTCG M40		
4,6	3		M3234GBD	LTCG 3/4	M3222GBD	LTCG 21	M4344GBD	LTCG M25		
			M3234GBE	LTCG 3/4	M3222GBE	LTCG 21	M4344GBE	LTCG M25		
5,0	2		M3231GAC	LTCG 1/2	M3216GAC	LTCG 13	M4340GAC	LTCG M20		
			M3234GAD	LTCG 3/4	M3222GAD	LTCG 21	M4344GAD	LTCG M25		
5,2	2	UL	M3231GAE†	LTCG 1/2	M3216GAE	LTCG 13	M4340GAE††	LTCG M20		
			3	UL	M3234GAF†	LTCG 3/4	M3222GAF	LTCG 21	M4344GAF	LTCG M25
					4	UL	M3234GAG†	LTCG 3/4	M3222GAG	LTCG 21
5,6	3	UL	M3200GAH†	LTCG LL 1/2	M3219GAH	LTCG 16	M3198GAH	LTCG LL M20		
6,0	2		M3200GAJ	LTCG LL 1/2	M3219GAJ	LTCG 16	M3198GAJ	LTCG LL M20		
			4	M3234GBC	LTCG 3/4	M3222GBC	LTCG 21	M4344GBC	LTCG M25	
6,5	6		M8437GAL	LTCG 1	M3225GAL	LTCG 29	M4348GAL	LTCG M32		
			M4524GAL	LTCG 1-1/4	M3204GAL	LTCG 36	M4352GAL	LTCG M40		
7,0	3		M3234GAM	LTCG 3/4	M3222GAM	LTCG 21	M4344GAM	LTCG M25		
7,4	2		M3234GAN	LTCG 3/4	M3222GAN	LTCG 21	M4344GAN	LTCG M25		
8,0	2		M3234GAQ	LTCG 3/4	M3222GAQ	LTCG 21	M4344GAQ	LTCG M25		
			6	M4524GAR	LTCG 1-1/4	M3204GAR	LTCG 36	M4352GAR	LTCG M40	
9,0	4		M8437GAS	LTCG 1	M3225GAS	LTCG 29	M4348GAS	LTCG M32		
			5	M4524GAT	LTCG 1-1/4	M3204GAT	LTCG 36	M4352GAT	LTCG M40	
			7	M4524GAW	LTCG 1-1/4	M3204GAW	LTCG 36	M4352GAW	LTCG M40	
9,5	4		M8437GAX	LTCG 1	M3225GAX	LTCG 29	M4348GAX	LTCG M32		

- Heyco® Multi-hole glands provide the widest range of conductor through-hole size and number configurations, many of which are agency approved. See the tabular charts for specific approvals for specific parts. These approvals are not “global” or implied approvals; they are both real and part specific.
- Integral Sealing Ring ensures a superior seal at the clearance or threaded mounting hole location, every time.
- IP 68 rated.
- Cordgrips are made of nylon construction with TPE sealing glands that resist salt water, weak acids, gasoline, alcohol, oil, grease, and common solvents.
- For body part dimensions see page 3-1, 3-3, and 3-4.
- Multi-hole glands are only to be used with Heyco Liquid Tight Cordgrips and are not sold separately.
- Consult Heyco for Cordgrips molded in other colors.

Standard color black.

\*Locknuts not included. For Locknut specifications or to order Locknuts separately, see pages 3-47 & 3-48.

\*\*Unassembled Nylon Locknuts INCLUDED.

†Assembled Metal Locknut INCLUDED

††M4340GAE is UL approved under File E51579



Material	Nylon 6/6 with TPE Sealing Gland
Certifications	UL Listed under Underwriters' Laboratories File E51579
Flammability Rating	94V-2 Standard
Temperature Range	Static -40°F (-40°C) to 239°F (115°C) Dynamic -4°F (-20°C) to 212°F (100°C)
IP Rating	IP 68

Quick  
Specs