Pan-Steel® Custom Length Banding – MBS, MBH, MBEH and MBSH Series

	Max. Bundle Diameter		Length*		Min. Loop Tensile Strength**		Min. Bundle Diameter		Width		Thickness^		Recommended Installation	Recommended Banding	Std. Pkg.
Part Number	ln.	In. mm		m	Lbs.	N	ln.	mm	In. mm		In. mm		Tool***	Head	Qty.‡
Polyester Coat	ed Al	SI 316	Stair	nless	Steel									,	
Heavy Cross Sec	tion														
MBCH-QR316	Any	Any	82	25	250	1112	0.50	12.7	0.31	7.9	0.010	0.25	GS4MT, ST2MT, HTMT, PPTMT, PBTMT	MTHCH-C316	1
Extra-Heavy Cros	ss Sec	tion												,	
MBCEH-QR316	Any	Any	82	25	300	1335	1.00	25.4	0.50	12.7	0.010	0.25	ST2MT, RT2HT, RT2HTN, PBTMT	MTHCEH-C316	1
Super-Heavy Cro	ss Se	ction													
MBCSH-QR316	Any	Any	82	25	450	2000	1.00	25.4	0.63	15.9	0.015	0.38	RT2HT, RT2HTN, PBTMT	MTHCSH-C316	1

^{*}Other lengths available, contact Panduit Customer Service.

To determine the proper amount of banding required, use the following formula:


Ca	Ilculate S and H Cross Section	Diameter inches (mm) x 3.14 + 3 inches (76mm)
Calcu	ılate EH and SH Cross Section	Diameter inches (mm) x 3.14 + 4.5 inches (114mm)

Pan-Steel® Custom Length Banding Heads – MTH Series


• Self-locking head design speeds installation and locks into place at any length along the tie body



		Std. Pkg.	Std. Ctn.				
Part Number	Part Description	Qty.	Qty.				
AISI 304 Stainless Steel							
MTHS-C	Loose piece banding head for standard cross section banding.	100	1000				
MTHH-C	Loose piece banding head for heavy cross section banding.	100	1000				
MTHEH-C	Loose piece banding head for extra-heavy cross section banding.	100	1000				
MTHSH-C	Loose piece banding head for super-heavy cross section banding.	100	1000				
AISI 316 Stainless Steel							
MTHS-C316	Loose piece banding head for standard cross section banding.	100	1000				
MTHH-C316	Loose piece banding head for heavy cross section banding.	100	1000				
MTHEH-C316	Loose piece banding head for extra-heavy cross section banding.	100	1000				
MTHSH-C316	Loose piece banding head for super-heavy cross section banding.	100	1000				
AISI 316 Coated Stainless Steel							
MTHCH-C316	Loose piece coated banding head for heavy cross section banding.	100	1000				
MTHCEH-C316	Loose piece coated banding head for extra-heavy cross section banding.	100	1000				
MTHCSH-C316	Loose piece coated banding head for super-heavy cross section banding.	100	1000				



1) Take one end of the cut banding and bend back 1/2" (13mm).



 Take a self-locking head and slide it the entire length of the band until it reaches the bend.



 Bend tail flat against bottom of banding head to complete assembly.

A. System Overview

B1. Cable Ties

B2. Cable Accessories

B3. Stainless Steel Ties

> C1. Wiring Duct

C2. Surface Raceway

C3. Abrasion Protection

C4. Cable Management

D1. Terminals

D2. Power Connectors

D3. Grounding Connectors

E1. Labeling Systems

> E2. Labels

E3. Pre-Printed & Write-On Markers

E4. Permanent Identification

E5. Lockout/ Tagout & Safety Solutions

> F. Index

^{**}Per SAE Standard AS23190/3 (formerly MIL). For additional details, refer to page B3.32.

^{***}For information on installation tools, refer to pages B3.14 – B3.16.

[^]Base material less coating

[‡]Order in number of reels required.