# MicroClick torque wrenches. Precision tools with high accuracy (tolerance of +/- 3%



Ratchet mechanism with reversing lever for clockwise and anticlockwise rotation. Automatic quick release: Clearly audible and palpable click signal when selected



Clearly legible analogue display for simple pre-selection of the desired torque.

Ergonomically shaped handle allows for automatically gripping it in a centric position. Important for obtaining an exact release torque.

Additional micro-scale for fine adjustment.

Simple pre-setting of the torque by turning the knurled ring at the end of the handle, fixing it by sliding it into position.



Note:

IMPACT sockets for wheel nuts are featured on page 16!

Piece by piece calibration and

permanent laser-marked serial number identifying the product.

final inspection. With

Practical release mechanism: the socket is securely fixed and automatically released at the push of the button.

Sturdy, oval steel shaft with rust-protective finish: double nickel and subsequent matt-finished chrome-plating.

MC 320

MC 200

### MicroClick MC 320. For 60 - 320Nm.

With 1/2" square drive (12.5mm). Total length 610mm. Otherwise as decribed above.

NO 23 354

#### MicroClick MC 200. For 40 - 200Nm.

With 1/2" square drive (12.5mm). Total length 530mm. Otherwise as described above.

NO 23 353

## MicroClick MC 100. For 20 - 100Nm.

With 3/8" square drive (10mm). Total length 430mm.
Particularly suitable for motorcycles. Otherwise as described above.
NO 23 351

#### MicroClick MC 30. For 6 – 30Nm.

With 1/4" square drive (6.3mm). Total length 335mm. Otherwise as described above. **NO 23 349** 







For full professional use!