


## Base strip - MCD 1,5/ 6-G-3,81 - 1829992

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 6, Pitch: 3.81 mm, Color: green, Contact surface: Tin, Mounting: Wave soldering, In combination with MCV plug components, both an MCVW and an MCVR plug must be used.


The figure shows a 10-pos. version with 20 contacts

### Product Features

- With offset levels
- Low-profile double-level pin strips with high contact density
- Improved view and access to lower level
- Plug-in direction parallel to the PCB



### Key Commercial Data

|                                      |   |
|--------------------------------------|---|
| Packing unit                         | 1 pc  |
| GTIN                                 | <br>4 017918 113704 |
| Weight per Piece (excluding packing) | 5.39 g  |
| Custom tariff number                 | 85366990  |
| Country of origin                    | Germany   |

### Technical data

#### Dimensions

|                          |          |
|--------------------------|----------|
| Length                   | 21.9 mm  |
| Pitch                    | 3.81 mm  |
| Dimension a              | 19.05 mm |
| Constructional height    | 23 mm    |
| Length of the solder pin | 3.5 mm   |

## Base strip - MCD 1,5/ 6-G-3,81 - 1829992

### Technical data

#### Dimensions

|                |              |
|----------------|--------------|
| Pin dimensions | 0,8 x 0,8 mm |
| Hole diameter  | 1.2 mm       |

#### General

|  |               |
|--|---------------|
| Range of articles                      | MCD 1,5/...-G |
| Insulating material group              | I             |
| Rated surge voltage (III/3)            | 2.5 kV        |
| Rated surge voltage (III/2)            | 2.5 kV        |
| Rated surge voltage (II/2)             | 2.5 kV        |
| Rated voltage (III/3)                  | 160 V         |
| Rated voltage (III/2)                  | 160 V         |
| Rated voltage (II/2)                   | 320 V         |
| Connection in acc. with standard       | EN-VDE        |
| Nominal current I <sub>N</sub>         | 8 A           |
| Maximum load current                   | 8 A           |
| Insulating material                    | PA            |
| Flammability rating according to UL 94 | V0            |
| Color                                  | green         |
| Number of positions                    | 6             |

#### Standards and Regulations

|  |        |
|--|--------|
| Connection in acc. with standard       | EN-VDE |
|  | CSA    |
| Flammability rating according to UL 94 | V0     |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |
| eCl@ss 9.0 | 27440402 |

# Base strip - MCD 1,5/ 6-G-3,81 - 1829992

## Classifications

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002637 |
| ETIM 5.0 | EC002637 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11     | 39121409 |
| UNSPSC 12.01  | 39121409 |
| UNSPSC 13.2   | 39121409 |

## Approvals

### Approvals


#### Approvals


CSA / VDE Gutachten mit Fertigungsüberwachung / cUL Recognized / IECEx CB Scheme / CCA / EAC / cULus Recognized / EAC

#### Ex Approvals

#### Approvals submitted

### Approval details


|   |       |       |
|---|-------|-------|
| CSA  |       |       |
|   | B     | D     |
| Nominal current I <sub>N</sub>  | 8 A   | 8 A   |
| Nominal voltage U <sub>N</sub>  | 300 V | 300 V |

|   |     |
|---|-----|
| VDE Gutachten mit Fertigungsüberwachung  |     |
| Nominal current I <sub>N</sub>  | 8 A |


## Base strip - MCD 1,5/ 6-G-3,81 - 1829992

### Approvals

|                    |       |
|--------------------|-------|
| Nominal voltage UN | 160 V |
|--------------------|-------|

cUL Recognized 

|                    | B     | D     |
|--------------------|-------|-------|
| Nominal current IN | 8 A   | 8 A   |
| Nominal voltage UN | 300 V | 300 V |

IECEE CB Scheme 

|                    |       |
|--------------------|-------|
| Nominal current IN | 8 A   |
| Nominal voltage UN | 160 V |

CCA

|                    |       |
|--------------------|-------|
| Nominal current IN | 8 A   |
| Nominal voltage UN | 160 V |

EAC

cULus Recognized


|                    | B     | D     |
|--------------------|-------|-------|
| Nominal current IN | 8 A   | 8 A   |
| Nominal voltage UN | 300 V | 300 V |

EAC

### Drawings

# Base strip - MCD 1,5/ 6-G-3,81 - 1829992

Drilling diagram



Dimensional drawing

