

# MINI-BAT/24DC/1.3AH

Order No.: 2866417




<http://eshop.phoenixcontact.co.uk/phoenix/treeViewClick.do?UID=2866417>

Rechargeable battery module, lead AGM, VRLA technology, 24 V DC, 1.3 Ah.



Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation at <http://www.download.phoenixcontact.com>. The General Terms and Conditions of Use apply to Internet downloads.

## Commercial data

EAN	 4 046356 152112
Pack	1
Customs tariff	85072098
Country of Origin	CN
Catalog page information	Page 623 (IF-2011)

## Technical data

### Input data

Nominal input voltage	24 V DC
-----------------------	---------

### Output data

Nominal output voltage	24 V DC
Output current	max. 15 A
Connection in series	No
Output fuse	15 A

#### General data

IQ technology	No
Disposal	Used batteries must not be thrown away with household waste, they should instead be disposed of in accordance with applicable national regulations. They can also be returned to Phoenix Contact or the manufacturer.
Width	52 mm
Height	130 mm
Depth	110 mm
Net weight	1.7 kg
Degree of protection	IP20
Protection class	III
Ambient temperature (operation)	0 °C ... 40 °C
Ambient temperature (storage/transport)	0 °C ... 40 °C

#### Certificates

Certifications applied for: UL-EX LIS

---

#### Accessories

Item	Designation	Description
<b>Fuse</b>		
0913676	SI FORM C 15 A DIN 72581	Flat-type plug-in fuse, type C, color code: light blue, nominal current: 15 A
<b>General</b>		
2938196	QUINT-PS-ADAPTERS7/1	Assembly adapter for QUINT-PS... power supply on S7-300 rail
2853983	UTA 107	Universal DIN rail adapter, for screwing on switchgear
2938235	UWA 182/52	Universal wall adapter

**Drawings**

Block diagram

---



**Address**

PHOENIX CONTACT Ltd  
Halesfield 13  
Telford / Shropshire / TF7 4PG,England  
Phone 01952 681 700  
Fax 01952 681 799  
<http://www.phoenixcontact.co.uk>



Phoenix Contact Ltd.  
Technical modifications reserved;