

# Wireless Combination Pin/Pinless Moisture Meter

**Detachable pin/pinless sensors transmit data to the display**


And can be viewed from a remote location up to 65ft (20m) from the measurement point

## Features:

- Full color graphical display
- Detachable sensors transmit data to the display that can be viewed from a remote location up to 65ft (20m) from the measurement point
- Connect to multiple sensors on individual channel
- Trending Mode with graphical representation of live reading for fast scanning of large areas
- Wireless sensor affixes to telescoping handle (4ft/1.2m) for measurements in ceilings or in hard to reach areas; Optional 9.8ft (3m) and 16.4ft (5m) handles available
- %WME (wood moisture equivalent) pin moisture reading
- Visual and audible High/Low alarm modes
- Pinless measurement depth to 0.75" (22mm) below the surface
- 2 point calibration check built into protective cap
- Cap protects pins during storage and snaps on to the side when in use
- Complete with 3.7V rechargeable Li-Polymer battery, wireless moisture sensor, external pin probe, replacement pins, telescoping handle (4ft/1.2m), AC adaptor, protective cap, 2G SD card, and hard case



Wireless sensor affixes to telescoping handle



## Ordering Information:

- M0270** .....Wireless Combination Pin/Pinless Moisture Meter  
**M0270-X** .....Optional Wireless Moisture Sensor  
**MO-P1** .....Remote Moisture Pin Probe for M0270  
**EXT-1** .....Telescoping Handle (extends to 4ft/1.2m) for M0270  
**EXT-3** .....Telescoping Handle (extends to 9.8ft/3m) for M0270  
**EXT-5** .....Telescoping Handle (extends to 16.4ft/5m) for M0270  
**M0200-PINS** .....Replacement Pins (50 Pins)

## Specifications

Pinless Range/Depth	0 to 99.9 (relative)/ 0.75" (22mm)
Pin Range	6.0 to 99.9%
Transmission Frequency	2.4GHz (pin/pinless sensor to display)
Transmission Range	65ft (20m) unobstructed view
Dimensions	8x2.3x1.7" (203x58.4x43.2mm)
Weight	7.2oz (204g)

