Power Film Capacitors - Screw/Stud Terminals

multicomp PRO

RoHS Compliant



Features


- · Conduction cooled
- Polypropylene dielectric
- · Self-healing
- Operating frequency up to 700kHz
- · Maximum operating core temperature 85°C
- Capacitance tolerance ±10%
- Flame retardant UL94- V0


Standard Capacitor Values

Part Number	Rated Voltage Vrms	Nominal Capacitance µF at 1kHz	Max Current Irms	Max Power Kvar	Frequency kHz	ESR mΩ	Dimensions mm		
							В	Н	L
MP004053	600	1.2	650	300	111-187	0.5	34	50	50
MP004051	700	0.33	500		295-401	1			
MP004052		0.66			147-200	8.0			

Capacitor Drawing and Terminal Style

Terminal Style: 5H





Tightening torque 20Nm max.

Dimensions: Millimetres


Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro




Power Film Capacitors - Screw/Stud Terminals


multicomp PRO


Frequency Derating







Voltage









Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro


multicomp PRO


Power Film Capacitors - Screw/Stud Terminals

multicomp PRO


Current

Frequency Derating





Voltage



Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

