


BNC Jack Crimp



Specifications:

Connector Type	: BNC Coaxial
Body Style	: Straight Jack
Coaxial Termination	: Crimp
Impedance	: 50Ω
Coaxial Cable Types	: RG-58
Contact Material	: Beryllium Copper
Contact Plating	: Silver
Frequency Max	: 11GHz
Connector Mounting	: Cable
Cable Diameter Max	: 5mm
Contact Material	: Brass
Contact Resistance	: 1.5mΩ
DC Current Max	: 1A
Insulator Material	: PTFE
Material	: Brass with Silicone Gasket
Operating Temperature	: -65°C to +165°C
Proof Voltage	: 2kV
Termination Method	: Crimp
VSWR	: 1.35
Working Voltage	: 500V

Diagram



No.	Description	Material	Finish
1	Crimp Ferrule	Brass	Silver 70μ" Min.
2	Centre Contact	Beryllium Copper	
3	Insulation	PTFE	None
4	Body	Brass	Silver 70μ" Min.
5	Chassis		

Part Number Table

Description	Part Number
Jack BNC, Crimp, 50R	MP-13-15-1 TSS RG58U

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.