


MPCH1040LR68

Aliases (UPIC1040LR6800)

KEMET, MPCH, Power, 0.68 uH, 20%, 1040(4340)



Click here for the 3D model.

Dimensions	
L	11.5mm MAX
W	10mm +/-0.3mm
Т	4mm MAX
LL	2.1mm NOM
G	3mm +/-0.5mm

Packaging Specifications	,
Packaging	T&R, 330mm
Packaging Quantity	1000

General Information	
Series	MPCH
Style	SMD
Chip Size	1040(4340)
Description	Surface Mount Inductor
Features	Large Current Inductors
RoHS	Yes
Core	Composite
Miscellaneous	40 (K) Temperature Rise Max.

Specifications		
Inductance	0.68 uH (0.1 MHz)	
Inductance	20%	
Tolerance	20%	
Temperature	-40/+125°C	
Range		
Rated	120°C	
Temperature	120 C	
Shielded	Yes	
Current	24 A (Isat, 20% Drop In Inductance), 22 A (Irms,	
Current	40C Rise By Self Heating)	
DC Resistance	2.3 mOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.