

MPQSIM Power Quality Simulator



- **Ideal for power quality training**
- **Easily create sags, swells, transients and harmonic events**
- **Simulate voltage flicker, leading and lagging power**
- **Create phase shift events**
- **Simulate three phases of voltage and current at 115 V ac or 230 Vac**
- **Operates off single-phase voltage**

DESCRIPTION

The MPQSIM Megger Power Quality Simulator is used for demonstrations and as a training tool. It is the perfect tool to use with the MPQ and PA9 Series.

The MPQSIM provides a simple and easy method for simulating a three-phase voltage configuration off of a standard single-phase source. The simulator provides both continuous voltages/currents and harmonics for trending as well as instantaneous events for power quality demonstrations and training.

APPLICATIONS

The MPQSIM Power Quality Simulator is ideal for power quality training courses and demonstrations of power quality phenomenon. The MPQSIM will allow you to see signatures of different types of power quality phenomenon. It also allows you to learn how to program a power quality analyzer to capture these phenomenon.

SPECIFICATIONS

Voltage Channels

3 Channels arranged in a wye configuration

Voltage Range

98Vac – 132Vac on the 115Vac Range
196Vac – 264Vac on the 230Vac Range

Voltage Accuracy

85.0 % +/- 0.5%
102.0% +/- .2%
115.0% +/- 0.5%

Current Channels

3 channels

Current Range

10A / 100A / 1000A / 6000A

Current Output is 0-1Vac Full Scale

0.45 Vac – 1.00 Vac full scale

Current Accuracy

+/-2% Full Scale

Output Frequency

50 Hz / 60 Hz

Phase Angle Range

-30° to +11°

Phase Angle Accuracy

±1.5°

Harmonic Orders

1st / 3rd & 5th



Simulated Phenomenon

- Sags / Dips
- Swells
- Transients
- Harmonics
- Phase Angle Shifts
- IEC Flicker
- Source Direction Reversal
- Leading and Lagging Power Factor
- AC Adapter power 100-240 Vac 50/60 Hz

Input

12VDC AC Adapter

Temperature

- Operating: 32° F to 105° F (0° C to 40° C)
- Storage: -5° F to 122° F (-20° C to 50° C)
- Humidity: 0 to 95% RH, noncondensing

Altitude

2000m

Standards

Safety - IEC 61010

CAT II @ 300V

IP40

Dimensions

- 14.2 L x 12 W x 7.6 H in. (36 L x 31 W x 19 H cm) Closed
- 14.2 L x 12 W x 5.4 H in. (36 L x 31 W x 14 H cm) Open

Weight

11.5 lbs (5.2 kg)

Call Us 1.877.571.7901

ORDERING INFORMATION	
Item (Qty)	Cat. No.
MPQ Simulator	1007-055
AC adapter	90017-548
Current cables	2008-124

