

# CURRENT MEASUREMENT PROBES

## MR SERIES AC/DC CURRENT PROBES



### MODELS MR415 / 416 / 525 / 526

*General Purpose Hall Effect Current Probes for use with DMMs, Data Loggers and Power Analyzers.*

### SPECIFICATIONS

MODEL	MR415	MR416	MR525	MR526
<b>ELECTRICAL</b>				
<b>Current Range</b>	0.5 to 400A <sub>AC</sub> , 600A <sub>DC</sub>	0.5 to 40A <sub>AC</sub> , 60A <sub>DC</sub> & 0.5 to 400A <sub>AC</sub> , 600A <sub>DC</sub>	0.5 to 1000A <sub>AC</sub> , 1400A <sub>DC</sub>	0.5 to 100A <sub>AC</sub> , 150A <sub>DC</sub> & 0.5 to 1000A <sub>AC</sub> , 1400A <sub>DC</sub>
<b>Output Signal</b>	1mV/A via a 5ft (1.5m) lead	10mV/A & mV/A via a 5ft (1.5m) lead	1mV/A via a 5ft (1.5m) lead	10mV/A & 1mV/A via a 5ft (1.5m) lead
<b>Output Terminal</b>	4 mm safety banana plug			
<b>Frequency Range</b>	DC to 30kHz (-3dB) (depending of current value)			
<b>Phase Shift At 50/60Hz</b>	≤1.5°@ 400A	≤2.2°@ 40A ≤1.5° @ 400A	≤1.5°@ 800A	≤2°@ 100A ≤1.5° @ 800A
<b>Load Impedance</b>	>1MΩ and ≤100pF			
<b>Overload</b>	3000A <sub>DC</sub> or 1000A <sub>AC</sub> continuous for < 1kHz			
<b>Zero Adjust</b>	Automatic on both ranges			
<b>Power Supply</b>	9V alkaline Battery (NEDA 1060A, 6LR61) or 5V DC Micro-USB type B			
<b>Battery Life</b>	50H typical			
<b>Low Battery Indication</b>	Green LED blinking			
<b>Overload Indication</b>	Red LED on when measurement > than selected range			
<b>MECHANICAL</b>				
<b>Maximum Conductor Size</b>	1.18" (30mm) or 2 bus bar 1.24 x 0.39" (31.5 x 10mm)		1.53" (39mm) or 2 bus bar 1.96 x 0.19" (50 x 5mm)	
<b>Dimensions (H x W x D)</b>	8.82 x 3.82 x 1.73" (224 x 97 x 44mm)		9.31 x 3.82 x 1.73" (236.5 x 97 x 44mm)	
<b>Weight (with Battery)</b>	0.98lbs (440g)		1.15lbs (520g)	
<b>ENVIRONMENTAL</b>				
<b>Operating Temperature</b>	14° to +131°F (-10 to +55°C)			
<b>Storage Temperature</b>	-40° to +176°F (-40 to +80°C)			
<b>Relative Humidity</b>	Up to 85% @ 35°C			
<b>SAFETY</b>				
<b>Ingress Protection</b>	IP 40			
<b>EMC</b>	EN 61326-1			
<b>Electrical</b>	IEC 61010-1, EN 61010-2-32, Pollution Degree 2, 600V CAT III			



### FEATURES

- The jaw shape enables users to clamp on to cables or small busbars
- Powered by battery or standard external 5V power supply via micro-USB connector
- Measures up to 1000A<sub>AC</sub> and 1400A<sub>DC</sub> (model dependent)
- Automatic Zero DC reset function
- Auto Power Off enable/disable function
- Millivolt output compatible with most equipment and instruments
- Battery life up to 50 hours
- Safety rating 600V CATIII

CATALOG NO.	DESCRIPTION
1200.80	AC/DC Current Probe Model MR415 (400AAC, 1mV/A & 600ADC, 1mV/A, 4mm Banana Plug Lead) Replaces MR410
1200.82	AC/DC Current Probe Model MR416 (40AAC, 60ADC, 10mV/A & 400AAC, 600ADC, 1mV/A, 4mm Banana Plug Lead) Replaces MR411
1200.81	AC/DC Current Probe Model MR415 (1000AAC, 1mV/A & 1400ADC, 1mV/A, 4mm Banana Plug Lead) Replaces MR520
1200.83	AC/DC Current Probe Model MR526 (100AAC, 150ADC, 10mV/A & 1000AAC, 1400ADC, 1mV/A, 4mm Banana Plug Lead) Replaces MR521

Rev.00 06/2020

