

MSPM101CS104 Product Details

[Share](#) | [Print](#) | [Email](#)


MSPM101CS104
(1825539-4)

TE Internal Number: 1825539-4

Active

Pushbutton Switches

[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Switch
- Not Tactile
- Single Pole - Single Throw Configuration (Pole-Throw)
- Contact Rating = 1.0 VA optimum [100mA max., 50 VDC max.]
- Process Sealed

[View all Features](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- [PUSH BUTTON SWITCH, MAGNETIC REED, HERMETICALLY SEAL...](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Switch
- Tactile = No
- Configuration (Pole-Throw) = Single Pole - Single Throw
- [Series](#) = MSPM
- Mount Angle = Vertical
- Termination Type = Wire Lugs
- Actuator Style = Plunger

Electrical Characteristics:

- Contact Rating = 1.0 VA optimum [100mA max., 50 VDC max.]

Body Features:

- Mount Style = Panel
- Actuator Length (mm [in]) = 4.06 [0.160]
- Actuator Profile = Extended
- Actuator Color = Red
- Bushing Diameter = 1/4-40
- Case Material = Steel
- Actuator Material = Polyamide

Contact Features:

- Contact Plating = Gold over Nickel

Housing Features:

- Process Sealed = Yes
- Low Profile = No
- Bushing Style = Threaded

Configuration Features:

- Operating Function = Normally Open, Momentary
- Ganged = No
- ESD Grounding Terminal = Without
- Actuator Force (g [oz]) = 113.40 - 198.50 [4.000 - 7.000]
- Number of Actuators = Single
- Illuminated = No
- Dust Proof = No
- Support Bracket = Without
- Snap Action = Without
- Detent Style = Audible

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Hand solderable with lead free solder
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- Temperature Rating = Standard

Packaging Features:

- Packaging Method = Loose Piece

Other:

- Brand = Alcoswitch

Corporate Information

[Who We Are](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)

Quick Links

[Check Distributor Inventory](#)
[Cross Reference](#)
[Find Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Search Knowledge Base](#)
[Manage your Account](#)

Keep Me Informed

Receive TE News, Events & Technology Updates

