

Control Power Transformer, 75va, PRI 120x240v, SEC 24v,  
Domestic,



Figure similar

Product brand name	Control Power Transformer
Product designation	MT
Special product feature	Robust design

General technical data	
Weight [lb]	3.5 lb
Height x Width x Depth [in]	3.46 × 3 × 4.1 in
Ambient temperature [°F] during operation	-4 ... +104 °F
Ambient temperature during operation	-20 ... +40 °C
Country of origin	Mexico
Operating apparent output rated value	75 V·A

Enclosure	
Design of the housing	Open

Mounting/wiring	
Mounting position	Any
Mounting type	Surface mounting
Type of electrical connection at output for main current circuit	Screw-type terminals (touchsafe)

Type of electrical connection at input for main current circuit	Screw-type terminals (touchsafe)
---	----------------------------------

### Inputs/ Outputs

Input dimensions of primary voltage	120x240vac
Output dimensions of secondary voltage	24vac
Phase number of the inputs	1
Electrical input frequency	50 ... 60 Hz
Input voltage _1	120 V
Input voltage _2	240 V
Phase number of the outputs	1
Electrical output frequency	60 ... 50 Hz
Output voltage _1 rated value	24 V

### Further information

**Industrial Controls - Product Overview (Catalogs, Brochures,...)**

[www.usa.siemens.com/iccatalog](http://www.usa.siemens.com/iccatalog)

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:MT0075C>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/US/en/ps/US2:MT0075C>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:MT0075C&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:MT0075C&lang=en)

last modified:

06/26/2018