

Down-Angle Cat6 Gigabit Molded UTP Ethernet Cable (RJ45 Right-Angle Down M to RJ45 M), Blue, 5 ft. (1.52 m)

MODEL NUMBER: N204-005-BL-DN



Highlights

- Space saving design
- Right Angle Down connector to Straight
- Cat6 Gigabit rated

System Requirements

- Use with Cat6, Cat5e, cat5, or VoIP Networks

Package Includes

- 5-ft. (1.52 m) Blue Cat6 Right Angle Down to Straight RJ45 - RJ45 Patch cable

Features

- 5-ft. (1.52 m) Blue Cat6, Right Angle Down to Straight RJ45 - RJ45 Patch cable
- PVC 4 Pair Stranded Conductors, 24AWG
- Fully Molded Ends
- ETL Verified to TIA/EIA -56b-B
- 550Mhz Gigabit Speed rated

Specifications

| OVERVIEW | |
|---------------------------|-----------------|
| UPC Code | 037332167545 |
| Technology | Cat6 |
| PHYSICAL | |
| Color | Blue |
| Cable Shielding | UTP |
| Cable Jacket Material | PVC |
| Cable Jacket Rating | CM |
| Number of Conductors | 4 Pair |
| Cable Outer Diameter (OD) | 6.0mm |
| Conductor Material | Stranded Copper |



| | |
|-----------------------------------|------------------------------|
| Conductor Gauge | 24 AWG |
| Cable Length (ft.) | 5 |
| Cable Length (m) | 1.5 |
| Cable Length (in.) | 60 |
| Cable Length (cm) | 152.4 |
| Shipping Dimensions (hwd / cm) | 0.64 x 17.78 x 25.40 |
| Shipping Dimensions (hwd / in.) | 0.25 x 7.00 x 10.00 |
| Shipping Weight (kg) | 0.05 |
| Shipping Weight (lbs.) | 0.10 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 14 to 122 F (-10 to 50 C) |
| Storage Temperature Range | 5 to 140 F (-15 to 60 C) |
| Operating Humidity Range | 0% to 90% RH, Non-Condensing |
| Storage Humidity Range | 0% to 90% RH, Non-Condensing |
| COMMUNICATIONS | |
| Bandwidth per TIA Standard | 250 MHz |
| Maximum Bandwidth as Tested | 500 MHz |
| Network Compatibility | 1Gbps |
| IEEE Standards Supported | 802.3an |
| CONNECTIONS | |
| Side A - Connector 1 | RJ45 (MALE) |
| Side B - Connector 1 | RJ45 (MALE) - DOWN ANGLE |
| Crossover Wiring | No |
| Contact Plating | Gold |
| Connector Type | Molded |
| Wiring Configuration | EIA/TIA 568B |
| SPECIAL FEATURES | |
| IP68 Rated | No |
| Snagless Connector | No |
| Antibacterial | No |
| STANDARDS & COMPLIANCE | |
| Certifications | RoHS, REACH |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| WARRANTY | |
|-------------------------------------|---------------------------|
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>