



NOTES:

- 1. Material: Corrosion resistant steel (CRES) per ASTM A582/A582M, type 303 (UN S30330) or 303SE (UNS S30323) or XM-1 (UMS S20300), condition A
- 2. Finish: Passivate per AMS2700, Method 1, Class 4
- 3. All Drawing Dimensions are in Inches [mm]
- 4. Unless otherwise specified, Edge Breaks, Radii or Countersinks 0.005-0.015
- 5. All features in accordance with NAS1831



95 Silvermine Rd., Seymour CT 06483 Tel: 203-888-2133, Fax: 203-888-9860 This Drawing is the Property of RAF. It contains confidential, proprietary information that is RAF property. Do not disclose to or duplicate for others except as authorized by RAF.

TOLERANCES
ALL DIMENSIONS ARE INCHES
(UNLESS OTHERWISE SPECIFIED)
METALLIC
LENGTHS </=:6 INCHES ± 0.005

LENGTH >: 6 INCHES ± 0.010
DIAMETERS: ± 0.005
NON-METALLIC
LENGTH: ± 0.010 DIAMETERS: ± 0.010

LENGTH: ± 0.010 DIAMETERS: ± 0.

INTERNAL THREADS:

MINIMUM THREAD DEPTH

l .

COMPONENT

NAS1831C4C08

1/4 Female Female Standoff

FEMALE FEMALE STANDOFF
SCALE REV
4.00 04
SHEET

1 of 1