

Product Search Data Sheet


Note: This datasheet may be out of date. Please download the latest datasheet of NCU15XH103F60RC from the official website of Murata Manufacturing Co., Ltd. m/en-SG/products/productdetail?partno=NCU15XH103F60RC

NCU15XH103F60RC



Appearance & Shape





Packaging Information

Packaging	Specifications	Minimum Order Quantity	
RC	180mm Paper Tape	10000	



- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-constant
- 4. Flow / Reflow soldering possible
- 5. Lead is not contained in the product.

6. NCU series are recognized by UL/cUL (UL1434, File No.E137188).

	Applications
--	--------------

Limited Usage	Consumer Grade
Other Usage	1. Temperature compensation for transistor, IC and crystal oscillator in mobile communications 2. Temperature sensor for rechargeable batteries 3. Temperature compensation of LCD 4. Temperature compensation in general use of electric circuits

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Attention



Product Search Data Sheet

NCU15XH103F60RC

Note: This datasheet may be out of date. Please download the latest datasheet of NCU15XH103F60RC from the official website of Murata Manufacturing Co., Ltd. http://www.murata.com/en-SG/products/productdetail?partno=NCU15XH103F60RC

Specifications

Resistance (25°C)	10kΩ
Resistance Value Tolerance (at 25°C)	±1%
B-Constant (25/50°C)	3380K
B-Constant (25/50°C) Tolerance	±1%
B-Constant(25/80°C)(Reference Value)	3428K
B-Constant(25/85°C)(Reference Value)	3434K
B-Constant(25/100°C)(Reference Value)	3455K
Max. Voltage	5V
Maximum Operating Current (25°C)	0.1mA
Typical Dissipation Constant (25°C)	1mW/°C
Operating Temperature Range	-40°C to 125°C
Size Code (in mm)	1.0x0.5mm
Size Code (in inch)	0.4x0.2inch
Shape	SMD
Mass	0.0012g

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Attention


Product Search Data Sheet




NCU15XH103F60RC

Note: This datasheet may be out of date Please download the latest datasheet of NCU15XH103F60RC from the official website of Murata Manufacturing Co., Ltd. http:/ n/en-SG/products/productdetail?partno=NCU15XH103F60RC

Product Data





Resistance-Temperature Characteristics

Maximum Operating Voltage Reduction Characteristics

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.