4

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. PANDUIT P/N WE LIGHT 3.86 LB/10 PCS NKPP48HDY (1745.4 a/10 PCS) .92 -[23.4] NOTES: I. SEE CURRENT CATALOG FOR VARIOUS APPLICATIONS WITH THIS WIRING SYSTEM. 2. THE HIGH DENSITY PATCH PANEL IS DESIGNED FOR MOUNTING TO 19" UNIVERSAL RACKS. - 1.25 3. PACKAGE CONTENTS: i . 73 [31.8] -48 PORT STAMPING i + 1[43.8] -8 POSITION FACEPLATE - .62 (6) (ASSEMBLED TO PANEL) โเร.9โ -SCREW KIT (INCLUDES FOUR #12-24 SCREWS) -SCREW KIT (INCLUDES FOUR M6 SCREWS) 4. DIMENSIONS IN PARENTHESIS ARE IN METRIC. - 18.20 -[462.3] [482.6] MODEL FILENAME SIZE MO1688AA\_NKPP48HD\_ASMBL\_06.PRT DRAWING FILENAME M02479DT\_DC100\_00A.PRT NETKEY 48 PORT HIGH DENSITY MODULAR PATCH PANEL CUSTOMER DRAWING N/A UUU CORP. PRODUCT SPEC N/A TINLEY PARK, ILL 60477 WORK INSTRUCTION ALL DIMENSIONS ARE GIVEN IN INCHES, UNLESS OTHERWISE SPECIFIED. N/A DIMENSIONAL TOLERANCES ARE: 1.XXX) ± .0101.31 SCALE (.X) ± NONE (.XX) ±.03(.8) ANGLES ± PART NO. WATERIAL! DRAWN BY JsP NKPP48HDY STAMPING: 3-11-06 3-11-06 JsP RELEASED TO PRODUCTION 20 GAGE C.R.S. FACEPLATE: ABS 02479 - 100 DRAWING NO. CHK.D 02479-100 REV DATE BY CHK DESCRIPTION ECN - R ĆUST SUP ОТН

\_\_