
Spec Sheet

SMD Power Inductors (NR series S type)

NRS4010T4R7MDGG



Features

- Item Summary 4.7uH±20%, 0.95A, 4.0x4.0x1.0mm
- Lifecycle Stage
 - Mass Production
- Standard packaging quantity (minimum)
 Taping Embossed 5000pcs


■ Products characteristics table

Inductance	4.7 uH ± 20 %
Case Size (mm)	4.0x4.0
Rated Current (max)	0.95 A
Saturation Current (max)	0.95 A
Temperature Rise Current (max)	1.2 A
DC Resistance (typ)	0.14 Ω
DC Resistance (max)	0.168 Ω
LQ Measuring Frequency	100 kHz
Self Resonant Frequency (min)	47 MHz
Operating Temp. Range	-25 to +125 °C (Including-self-generated heat)
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (168 subst.)	Yes
Soldering	Reflow

External Dimensions

Dimension L	4.0 ±0.2 mm
Dimension W	4.0 ±0.2 mm
Dimension H	Max 1.0 mm
Dimension e	1.1 ±0.2 mm

Recommended Land Patterns



2016.05.21

SMD Power Inductors (NR series S type)

NRS4010T4R7MDGG



Dimension unit : mm unit: inch Length: 4.0 + / - 0.2(0.157 + / - 0.008)Width: 4.0 +/- 0.2 (0.157 + / - 0.008)max.) Height: 1.0 max. (0.039

Inductance: 4.7 иΗ (test freq at 0.1MHz) / 0.168 DC Resistance: 0.14 ohm (typ/max)

Saturation Current: 950 mA (max) 1,200 mA (max) Temp. rise Current:

> Saturation current typical: 30% reduction from initial L value. Temp rise Current typical: Temperature will rise by 40 deg C

